


TECHNICAL DATA

KÄHR'S LUXURY TILES

LOOSE LAY WOOD AND STONE



Loose Lay Stone 500 x 500 x 5.0 x 0.5 mm
2.5 m²/box






Loose Lay Wood 228.6 x 1219 x 5.0 x 0.5 mm
1.95 m²/box

PRODUCT












Loose Lay LVT	EN ISO 10582	Luxury Vinyl Tile
Application	EN ISO 10874	23/32



SPECIFICATION

Thickness		EN ISO 24337	5.0 mm
Weight		EN ISO 24342	9.7 kg/m ²
Wear layer		EN ISO 24346	0.5 mm

PRODUCT PROPERTIES

PROPERTY	TEST METHOD	RESULT
Indoor air certifications		M1, FloorScore, A+
Fire resistance	 EN 13501-1	B _{f1} -s1
Residual indentation	 EN ISO 24343-1	< 0.1 mm
Dimensional stability	 EN ISO 23999	≤ 0.15%
Colour fastness	 EN ISO 105-B02	≥ 6
Slip resistance	 EN 13893 DIN 51130	DS (> 0.3) R10
Electrical propensity	 EN 1815	< 2 kV (antistatic)
Wear and scratch resistance	 EN 660-2	< 2.0 mm ³ (Group T)
Chemical resistance	 EN ISO 26987	Pass with good results
Thermal resistance	 EN 12664:2001	0.013 m ² K/W
Effect of castor chair	 EN 425	Suitable
Underfloor heating		Ok (max +27 °C)
Resistance to bacteria and fungi		Good