

# TECHNICAL DATA






## ESTRAD UNI

### PRODUCT











Estrad Uni	EN ISO 10582	Unicolour sheet vinyl flooring for public spaces
Application	EN ISO 10874	23/34/43



### SPECIFICATION


Thickness		EN ISO 24346	2.0 mm
Weight		EN ISO 23997	2660 g/m <sup>2</sup>
Wear layer		EN ISO 24340	0.7 mm
Roll length		EN ISO 24341	20 m
Width		EN ISO 24341	2 m

### PRODUCT PROPERTIES


PROPERTY	TEST METHOD	RESULT
Indoor air certifications		M1, Floorscore
Fire resistance	 EN 13501-1	B <sub>f1</sub> -s1
Residual indentation	 EN ISO 24343-1	< 0.1 mm
Dimensional stability	 EN ISO 23999	< 0.4 %
Colour fastness	 ISO 105-B02	> 6 (Method 3)
Slip resistance	 EN 13893 DIN 51130	DS R10
Electrical propensity	 EN 1815	≤ 2 kV (antistatic)
Wear and scratch resistance	 EN 649	Class T
Chemical resistance	 EN 423	Excellent
Effect of castor chair	 EN 425/ ISO 4918	Suitable
Underfloor heating		Suitable (max +27 °C)




COLLECTION COLOURS  
**ESTRAD UNI**



15401



15402




15403



15404



15422



15424



15429



15406



15449



15454



15456



15464