

UPOFLOOR®

UPOFLOOR Transitional

UPOFLOOR Transitional is an acrylic-based adhesive formulated with high bond strength and shear resistance for installing UPOFLOOR Quartz, Xpression, Zero and Zero Tile flooring. UPOFLOOR Transitional offers excellent initial tack that transitions to a firmer bond and has very low odor for installations in health care facilities, schools, and offices. It is made with a broad spectrum antimicrobial to improve mold and fungal resistance.

Site Preparation: Suitable substrates include above, on or below grade concrete (within moisture and alkalinity specifications), APA underlayment grade plywood and radiant heated floors (85°F and below). All substrates must be flat, clean, smooth and dry, free of waxes, existing adhesives, dirt or dust, grease, oil, solvents, paint, curing compounds or sealers. Do not use on chemically cleaned substrates or over treated plywood substrates.

The installation site must be acclimated with HVAC in operation. The floor and room temperature, as well as flooring materials and adhesive, must be maintained at 65° - 85° F, and the humidity between 40% - 65% for 48 hours prior to, during, and after the testing and installation.

Installation: Flooring may be placed into adhesive after 10 - 25 minutes open time (flash-off) over a porous substrate, while the trowel ridges are still semi-wet, opaque, and transfer to the finger when touched. Loss of adhesion can result if the flooring is not installed within the working time of the adhesive. Working time is up to 1 hour depending on temperature, humidity, and substrate type. Roll the installation in both directions with a 100 lb. 3-section roller immediately after the flooring is placed and positioned, ensuring complete contact with the adhesive and transfer to the back of the flooring material.

Moisture Limits: 85% Relative Humidity as measured per the latest version of ASTM F2170, pH of 8.0 - 11.0. Impedance meter readings should not exceed 4%. All substrate preparation and testing procedures must conform to appropriate ASTM guidelines, and comply with the specific floor-covering specifications.

Trowel Size: 1/16" x 1/16" x 1/16" SQ-Notch (Coverage = 160 - 180 square feet per gallon) or 1/16" x 1/32" x 1/32" U-Notch (Coverage = 220 - 260 square feet per gallon).

Traffic: Restrict foot traffic, furniture placement, and rolling loads for 24 hours after installation. Additional time may be necessary if the installation is over a non-porous substrate. Allow at least five days following the installation before conducting wet cleaning procedures or initial maintenance.

Clean Up: Use a clean wet cloth to clean up adhesive while still wet; dried adhesive may require the use of an appropriate solvent.

Shelf Life: 1 year from manufacturing date in unopened, properly stored container. Avoid excessive heat or cold. Protect from freezing.

Certifications and Indoor Health:

- IEQ Credit 2.1, 2.2; Low Emitting Materials
- FloorScore certified
- VOC Content is below that established by California SCAQMD Rule 1168
- California Section 01350 compliant

Disclaimer: Users should determine the suitability of this information or product for their own purpose or application. Manufacturer is not responsible for the misuse of this product. This Technical Data sheet and the information conveyed herein supersede all previous versions. 1/21/2020

Upofloor America's Inc.

940 Centre Circle, Suite 1000
Altamonte Springs, FL 32714

Phone: 1 800 800 5247
Fax: 407 260 9933

www.upofloor.com