





# TECHNICAL DATA ESTRAD CLASSIC

## PRODUCT









Estrad Classic	EN ISO 10581	Homogeneous sheet vinyl for public spaces
Application	EN ISO 10874	23/34/43



## SPECIFICATION

Thickness	 EN ISO 24346	2.0 mm
Weight	 EN ISO 23997	2950 g/m <sup>2</sup>
Roll length	 EN ISO 24341	20 m
Width	 EN ISO 24341	2 m

## PRODUCT PROPERTIES

PROPERTY	TEST METHOD	RESULT
Indoor air certifications		M1, Floorscore
Fire resistance	 EN 13501-1	B <sub>fl</sub> -s1
Colour fastness	 ISO 105-B02	≥ 6
Slip resistance	 EN 13893 DIN 51130	DS R9
Electrical propensity	 EN 1815	≤ 2 kV (antistatic)
Wear and scratch resistance	 EN 660-2	Class T
Chemical resistance	 EN ISO 26987	Pass with good results
Effect of castor chair	 EN 425/ISO 4918	Suitable
Underfloor heating		Suitable (max +27 °C)

**Kährs®**

COLLECTION COLOURS  
**ESTRAD CLASSIC**



15101




15102



15103




15104



15106



15120



15152



15154