



OAK TUFT

Oak Tuft features a 1-strip design and matt finish. Apperance is rustic, with knots and color variations from light to dark.

PRODUCT DETAILS		PRODUCT D
Product type / Construction	Wood Flooring / 3-layer parquet	LRV / LRV Std
Article Number / EAN Code	13106AEK1BKW185 / 7393969043229	Warranty
Design / Wood Species	1-strip / Oak	— TECHNICAL
Surface treatment /	Matt lacquer / Stained	Moisture con
Natural/Stained		— Minimun Mea
Design features	Microbevelled 4-sided, Brushed	— kg/m³
Width x Length x Thickness	127 x 1860 x 13 mm	— Reaction To F
Weight per package / per	12.687 kg / 7.68 kg	Formaldehyd
m2		— Content PCP
Area per package / per	1.652 m ² / 104.076 m ²	
pallet		Breaking Stre
Grading	Lively	Thermal Cond
Joint	Woodloc® 5G	Thermal Resis
Installation method	Floating, Glue-down	Biological Dur
Floor heating	Yes	CARB2
Wear leayer material /	Hardwood / 3 mm	Slip resistance
thickness		TSCA
Resandable	2-3 times	CARB P2
Core material	Pine/Spruce lamella	Compliant
Brinell value / range	3,7 / 2.2 - 5.9	

PRODUCT DETAILS		
LRV / LRV Std1	24.9 / 3.1	
Warranty	25 years	
TECHNICAL PROPERTIES		
Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m³
kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 ppm
Breaking Strength N/mm ²	EN1533	NPD
Thermal Conductivity	EN12664	0,08 W/mK
Thermal Resistance R-Value		.15 (m2K/W)
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CEN/TS15676	NPD







DETAILED DESCRIPTION

All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

Colour change: Stained product - noticeable color change over time.

Packages may contain start and stop boards.

Other products in this collection

Oak Etch

Oak Tuft



Oak Mostra