



OAK KINDA

The earthen grey stain on this single-strip oak floor from the Småland Collection allows the warmer tones in the base to come through, resulting in a very rustic expression with a delicately balanced colour variation. Light and dark contrasts in the wood are punctuated with occasional saw marks, which give the floor its restored appearance. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided bevelling at the edges ensures a classic, full plank look and feel. Every board is meticulously hand-scraped, which enhances the rustic appearance of the floor.

PRODUCT DETAILS		
Product type / Construction	Wood Floors / 3-layer parquet	
Article Number / EAN Code	151NDSEK02KW240 / 7393969039031	
Design / Wood Species	1-strip / Oak	
Surface treatment /	Oil / Stained	
Natural/Stained		
Design features	Bevelled 4-sided, Handscraped, Brushed, Saw	
	marks	
Width x Length x Thickness	187 x 2420 x 15 mm	
Weight per package / per	22 kg / 8.15 kg	
m2		
Area per package / per	2.7 m ² / 122.4 m ²	
pallet		
Grading	Expressive	
Joint	Woodloc® 5S	
Installation method	Floating, Glue-down	
Floor heating	Yes	
Wear leayer material /	Hardwood / 3.5 mm	
thickness		
Resandable	2-4 times	
Core material	Pine/Spruce lamella	
Hardness (Brinell) value /	3,7 / 2.2 - 5.9	
range		

PRODUCT	DETAILS
---------	----------------

Warranty	30 years	
TECHNICAL PROPERTIES	5	
Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m³
kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 ppm
Breaking Strength N/mm ²	EN1533	NPD
Thermal Conductivity	EN12664	0,11W/mK
Thermal Resistance R-Value	2	.11 (m2K/W)
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CEN/TS15676	NPD

















DETAILED DESCRIPTION

All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur.

The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

Oil: This floor should be oiled immediately after installation.

Colour change: The colour matures over time.

Packages may contain start and stop boards.

Descriptions & Imagery

www.kahrs.com | [©]Kährs 2025-05-13

Other products in this collection



OAK KLINTA



OAK SEVEDE



OAK YDRE



OAK MÖRE



OAK VISTA



OAK VEDBO



OAK TVETA



OAK FINNVEDEN



OAK ASPELAND