



OAK KINDA

The earthen grey stain on this single-strip oak floor from the Småland Collection allows the warmer tones in the base to come through, resulting in a very rustic expression with a delicately balanced colour variation. Light and dark contrasts in the wood are punctuated with occasional saw marks, which give the floor its restored appearance. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided bevelling at the edges ensures a classic, full plank look and feel. Every board is meticulously hand-scraped, which enhances the rustic appearance of the floor.

PRODUCT DETAILS	
Article Number	151NDSEK02KW240
EAN Code	7393969039031
Surface treatment	Oil This floor should be oiled immediately after installation.
Design features	Bevelled 4-sided, Handscraped, Brushed, Saw marks
Dimensions	187 x 2420 mm
Weight per Package	22 kg
Area per Package	2.7 m²
Area per pallet	122.4 m²
Package info	Packages may contain start and stop boards.


DETAIL DESCRIPTION	
All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.	

COLOUR CHANGE	
The colour matures over time.	


FACTS	
Wood Species	Oak
Design	1-strip
Grading	Expressive
Range	Kährs Supreme
Collection	Småland Collection
Resandable	2-4 times
Natural/Stained	Stained
Brinell Value	3,7
Joint	Woodloc® 5S
Floor heating	Yes
Warranty	30 years
Wear-layer material	Hardwood
Wear Layer Thickness	3.5 mm
Core material	Pine/Spruce lamella
Thickness	15 mm
Installation method	Floating, Glue-down
Surface Colour	Earth Grey

TECHNICAL PROPERTIES		
Moisture content	EN13183	7%±2%
Minimum Mean Density kg/m³	>500 kg/m³	
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 ppm
Breaking Strength N/mm²	EN1533	NPD
Thermal Conductivity	EN12664	0,14 W/mK
Thermal Resistance R-Value	.11 (m2K/W)	
Biological Durability	EN350-2	Class 1
CARB2	Compliant	
Slipperiness	CEN/TS15676	NPD


Other products in this collection



Oak Klinta




Oak Sevede




Oak Ydre




Oak Möre




Oak Vista



Oak Vedbo



Oak Handbörd



Oak Tveta



Oak Finnveden



Oak Aspeland

CERTIFICATES



Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.