



OAK OUTPOST

The lightly smoked finish on this single-strip oak floor from the Habitat Collection enhances the grey and auburn hues in the timber. The naturally occurring knots and cracks highlight its rustic expression and add depth to the floor. Four-sided bevelling at the edges ensures a classic full plank look and feel. Each board is carefully brushed to bring out the character of the grain and the natural texture of the wood.

PRODUCT DETAILS

Product type / Construction	Wood Floors / Veneer floors
Article Number / EAN Code	37107AEKFMKW180 / 7393969107099
Design / Wood Species	1-strip / Oak
Surface treatment / Natural/Stained	Oil / Stained
Design features	Microbevelled 4-sided, Brushed, Light smoked
Width x Length x Thickness	150 x 1810 x 7 mm
Weight per package / per m2	20 kg / 6.06 kg
Area per package	3.3 m ²
Grading	Dynamic
Joint	Woodloc®
Installation method	Floating, Glue-down
Floor heating	Yes
Wear leayer material / thickness	Hardwood / 0.6 mm
Resandable	Not resandable
Core material	HDF
Hardness (Brinell) value / range	5 - 6 / 5 - 6

PRODUCT DETAILS

Warranty	12 years	
TECHNICAL PROPERTIES		
Moisture content	EN13183	7%±2%
Minimum Mean Density	>800 kg/m³	
kg/m³		
Reaction To Fire	EN13501-1	Cfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 ppm
Breaking Strength N/mm²	EN1533	NPD
Thermal Conductivity	EN12664	0,22 W/mK
Thermal Resistance R-Value	.031 (m2K/W)	
Biological Durability	EN350-2	Class 1
CARB2	Compliant	
Slip resistance	CEN/TS15676	NPD



DETAILED DESCRIPTION

All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur.
The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

Oil: This floor should be oiled immediately after installation.

Colour change: Stained product - noticable color change over time.

Packages may contain start and stop boards.

Descriptions & Imagery

