



OAK OUTPOST

Oak Outpost is a lightly smoked, brushed grey oiled rustic floor with cracks and knots that enhance the natural wood feeling.

PRODUCT DETAILS		FACTS		TECHNICAL PROPERTIES		
Article Number	37107AEKFMKW180	Wood Species	Oak	Moisture content	EN13183	7%±2%
EAN Code	7393969107099	Design	1-strip	Minimum Mean Density kg/m³ >800 kg/m³		
Surface Treatment	Oil This floor should be oiled immediately after installation.	Grading	Dynamic			
Refining Treatment	Microbevelled 4-sided, Brushed, Light smoked	Range	Kährs Linnea	Reaction To Fire	EN13501-1	Cfl-s1
		Collection	Habitat Collection	Formaldehyde Emission	EN717-1	E1
Dimensions	150 x 1810 mm	Natural/Stained	Stained	Content PCP	CEN/TR14823	≤ 5 x 10-6n
Weight per Package	20 kg	Brinell Value	5 - 6	Breaking Strength N/mm²	EN1533	NPD
Area per Package	3.3 m²	Joint	Woodloc®	Thermal Conductivity	EN12664	0,22 W/mK
Package info	Packages may contain start and stop boards.	Floor heating	Yes	Thermal Resistance R-Value		.031 (m2K/W)
DETAIL DESCRIPTION		Wear-layer material	Hardwood	Biological Durability	EN350-2	Class 1
		Wear Layer Thickness	0.6 mm	CARB2		Compliant
		Core material	HDF	Slipperiness	CEN/TS15676	NPD
			7 mm			
		Installation method	Floating, Glue-down			
		Surface Colour	Warm grey			

COLOUR CHANGE

Stained product - noticable color change over time.



Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.