



OAK WILDS

Oak Wilds is a lightly smoked, brushed oiled rustic floor with cracks and knots that enhance the natural wood feeling.

| PRODUCT DETAILS | | FACTS | | TECHNICAL PROPERTIES | | |
|---|---|----------------------|---------------------|----------------------------|--------------|-------------|
| Article Number | 37107AEKFCKW180 | Wood Species | Oak | Moisture content | EN13183 | 7%±2% |
| EAN Code | 7393969107082 | Design | 1-strip | Minimum Mean Density kg/m³ | >800 kg/m³ | |
| Surface Treatment | Oil This floor should be oiled immediately after installation. | Grading | Dynamic | | | |
| | | Range | Kährs Linnea | Reaction To Fire | EN13501-1 | Cfl-s1 |
| | | Collection | Habitat Collection | Formaldehyde Emission | EN717-1 | E1 |
| Refining Treatment | Microbevelled 4-sided, Brushed, Light smoked | Natural/Stained | Natural | Content PCP | CEN/TR14823 | ≤ 5 x 10-6n |
| Dimensions | 150 x 1810 mm | Brinell Value | 5 - 6 | Breaking Strength N/mm² | EN1533 | NPD |
| Weight per Package | 20 kg | Joint | Woodloc® | Thermal Conductivity | EN12664 | 0,22 W/mK |
| Area per Package | 3.3 m² | Floor heating | Yes | | | |
| Package info | Packages may contain start and stop boards. | Wear-layer material | Hardwood | Thermal Resistance R-Value | .031 (m2K/W) | |
| | | Wear Layer Thickness | 0.6 mm | Biological Durability | EN350-2 | Class 1 |
| | | Core material | HDF | CARB2 | Compliant | |
| DETAIL DESCRIPTION | | | 7 mm | Slipperiness | CEN/TS15676 | NPD |
| | | Installation method | Floating, Glue-down | | | |
| | | | | | | |
| COLOUR CHANGE | | | | | | |
| Some muting of colour variation to medium, straw brown. | | | | | | |



Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.