



OAK FINNVEDEN

This amber stained, single-strip oak floor from the Småland Collection allows the honey hues in the wood to seep through, resulting in a very rustic expression. Light and dark contrasts in the wood are punctuated with occasional saw marks, which give the floor its restored appearance. Four-sided bevelling at the edges ensures a classic, full plank look and feel. Each board is meticulously hand-scraped, which enhances the rustic appearance of the floor.

| PRODUCT DETAILS | | PRODUCT DE | |
|-----------------------------|---|-------------------------|--|
| Product type / Construction | Wood Flooring / 3-layer parquet | Brinell value / ra | |
| Article Number / EAN Code | 151NDSEK03KW240 / 7393969039048 | Warranty | |
| Design / Wood Species | 1-strip / Oak | - TECHNICAL P | |
| Surface treatment / | Oil / Natural | | |
| Natural/Stained | | Moisture conte | |
| Design features | Bevelled 4-sided, Brushed, Handscraped, Saw | - Minimun Mean kg/m³ | |
| | marks | - Reaction To Fire | |
| Width x Length x Thickness | 187 x 2420 x 15 mm | | |
| Weight per package / per | 22 kg / 8.15 kg | Formaldehyde I | |
| m2 | | Content PCP | |
| Area per package / per | 2.7 m ² / 122.4 m ² | Breaking Streng | |
| pallet | 2.7 7 .22 | Thermal Condu | |
| · | Everective | Thermal Resista | |
| Grading | Expressive | Biological Dural | |
| Joint | Woodloc® 5S | CARB2 | |
| Installation method | Floating, Glue-down | - Slip resistance | |
| Floor heating | Yes | Jilp resistance | |
| Wear leayer material / | Hardwood / 3.5 mm | TSCA | |
| thickness | | CARB P2 | |
| Resandable | 2-4 times | Compliant | |
| Core material | Pine/Spruce lamella | floor | |
| Backside material | Veneer | O STORY | |

| PRC | DU | CT | DE. | ΓΑΙ | LS |
|-----|----|----|-----|-----|----|
| | | | | | |

| Brinell value / range | 3,7 / 2.2 - 5.9 | |
|----------------------------|-----------------|-------------|
| Warranty | 30 years | |
| TECHNICAL PROPERTIES | 5 | |
| Moisture content | EN13183 | 7%±2% |
| Minimun Mean Density | | >500 kg/m³ |
| kg/m³ | | |
| Reaction To Fire | EN13501-1 | Dfl-s1 |
| Formaldehyde Emission | EN717-1 | E1 |
| Content PCP | CEN/TR14823 | ≤ 5 ppm |
| Breaking Strength N/mm² | EN1533 | NPD |
| Thermal Conductivity | EN12664 | 0,14 W/mK |
| Thermal Resistance R-Value | 2 | .11 (m2K/W) |
| Biological Durability | EN350-2 | Class 1 |
| CARB2 | | Compliant |









CEN/TS15676





NPD







DETAILED DESCRIPTION

All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur.

The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

Oil: This floor should be oiled immediately after installation.

Colour change: Stained product - noticable color change over time.

Packages may contain start and stop boards.

Descriptions & Imagery

www.kahrs.com | ©Kährs

Other products in this collection



Oak Klinta



Oak Sevede



Oak Ydre



Oak Möre




Oak Vista



Oak Vedbo



Oak Handbörd



Oak Tveta



Oak Finnveden



Oak Aspeland