



## **FINNVEDEN**

PRODUCT DETAILS		PRODUCT DETAILS
Product type / Construction	Wood Flooring / 3-layer engineered	Hardness (Brinell) value /
Article Number / EAN Code	151NDSEK03KW240 / 7393969039048	range
Design / Wood Species	1-strip / White Oak	- - TECHNICAL PROPERTIE
Surface Treatment /	Oil / Natural	Moisture content
Natural/Stained		- Minimun Mean Density
Refining Treatment	Beveled 4-sided, Brushed, Handscraped, Saw	kg/m <sup>3</sup>
	marks	- Reaction To Fire
Width x Length x Thickness	7 3/8 x 95 1/4 x 5/8"	- Formaldehyde Emission
Weight per package / per	48.5 lbs / 18 lbs	Content PCP
m2		- Breaking Strength N/mm <sup>2</sup>
Area per package / per	29.1 sqft / 1317.5 sqft	Thermal Resistance R-Valu
pallet		- Biological Durability
Grading	Expressive	- CARB2
Joint	Woodloc® 5S	-
Installation method	Floating, Glue-Down	- Slip resistance
Floor heating	Yes	TSCA SUMAN ECO. LITLE VI
Wear leayer material /	Hardwood / 1/8"	CARB P2
thickness		Compliant
Resandable	2 times	<del>-</del>
Core material	Pine/Spruce lamella	<del>-</del>
Backside material	Veneer	<del>-</del> -
·	·	

## PRODUCT DETAILS

3777212 313	
EN13183	7%±2%
	>500 kg/m³
EN13501-1	Dfl-s1
EN717-1	E1
CEN/TR14823	≤ 5 x 10-6n
EN1533	NPD
2	.11 (m2K/W)
EN350-2	Class 1
	Compliant
	EN13183  EN13501-1  EN717-1  CEN/TR14823  EN1533

3,7 / 2.2 - 5.9









CEN/TS15676



NPD

## DETAILED DESCRIPTION

All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur.

The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

Oil: This floor should be oiled immediately after installation.

**Colour change**: Stained product - noticable color change over time.

Packages may contain start and stop boards.

## Other products in this collection



Oak Klinta



Sevede



Ydre



Möre



Vista

Vedbo

Tveta



Finnveden



Aspeland