



FINNVEDEN

PRODUCT DETAILS		FACTS		TECHNICAL PROPERTIES			
Article Number	151NDSEK03KW240	Wood Species	White Oak	Moisture	EN13183	7%±2%	
EAN Code	7393969039048	Design	1-strip	content			
Surface Treatment	Oil This floor should be oiled immediately after installation.	Grading	Expressive	Minimun Mean	Minimun Mean Density kg/m³ >500 kg/m³		
		Range	Kährs Supreme	Reaction To Fire	EN13501-1	Dfl-s1	
		Collection	Småland Collection	Formaldehyde	EN717-1	E1	
Refining Treatment	Beveled 4-sided, Brushed, Handscraped, Saw marks	Resandable	2 times	Emission			
		Natural/Stained	Natural	Content PCP	CEN/TR14823	≤ 5 x 10-6n	
Dimensions	7 3/8 x 95 1/4 "	Brinell Value	3,7	Breaking Strength N/mm ²	EN1533	NPD	
Weight per Package	48.5 lbs	Joint	Woodloc® 5S				
Area per Package	29.1 sqft	Floor heating	Yes	Thermal	EN12664	0,14 W/mK	
Area per pallet	1317.5 sqft	Warranty	30 years	Conductivity			
Package info	Packages may contain start and stop boards.	Wear-layer material	Hardwood	Thermal Resista	Thermal Resistance R-Value		
		Wear Layer Thickness	1/8"	Biological Durability	EN350-2	Class 1	
DETAIL DESCRIPTION		Core material	Pine/Spruce lamella	CARB2		Compliant	
All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Knots and cracks will be		Backside material	Veneer	Slipperiness	CEN/TS15676	NPD	
		Thickness	5/8"			=	
		Installation method	Floating, Glue-Down				

COLOR CHANGE

present in all sizes and numbers.

Stained product - noticable color change over time.

Other products in this collection



CERTIFICATES

Finnveden









Aspeland



Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.