



## **OAK YDRE**

The smoked stone stain on this single-strip oak floor from the Småland Collection allows the cooler nuances in the base to come through, resulting in a smooth and harmoniously balanced expression. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided bevelling at the edges ensures a classic, full plank look and feel. Every board is meticulously hand-scraped, which enhances the worn appearance of the floor.

PRODUCT DETAILS			
Product type / Construction	Wood Floors / 3-layer parquet		
Article Number / EAN Code	151NCSEK04KW240 / 7393969038997		
Design / Wood Species	1-strip / Oak		
Surface treatment /	Oil / Stained		
Natural/Stained			
Design features	Bevelled 4-sided, Brushed, Light smoked,		
	Handscraped		
Width x Length x Thickness	187 x 2420 x 15 mm		
Weight per package / per	22 kg / 8.15 kg		
m2			
Area per package / per	2.7 m <sup>2</sup> / 122.4 m <sup>2</sup>		
pallet			
Grading	Dynamic		
Joint	Woodloc® 5S		
Installation method	Floating, Glue-down		
Floor heating	Yes		
Wear leayer material /	Hardwood / 3.5 mm		
thickness			
Resandable	2-4 times		
Core material	Pine/Spruce lamella		
Backside material	Veneer		

PRODUCT D	<b>ETAILS</b>
-----------	---------------

Hardness (Brinell) value /	3,7 / 2.2 - 5.9	
range		
Warranty	30 years	
TECHNICAL PROPERTIES		
- Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m³
- kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 ppm
Breaking Strength N/mm <sup>2</sup>	EN1533	NPD
Thermal Conductivity	EN12664	0,11W/mK
Thermal Resistance R-Value	!	.11 (m2K/W)
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CEN/TS15676	NPD



















## DETAILED DESCRIPTION

All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur.

The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

Oil: This floor should be oiled immediately after installation.

**Colour change**: Stained product - noticable color change over time.

Packages may contain start and stop boards.

Descriptions & Imagery

## Other products in this collection



OAK KLINTA



OAK SEVEDE



OAK YDRE



OAK MÖRE



OAK VISTA



OAK VEDBO



OAK TVETA



OAK FINNVEDEN



OAK ASPELAND