



OAK YDRE

The smoked stone stain on this single-strip oak floor from the Småland Collection allows the cooler nuances in the base to come through, resulting in a smooth and harmoniously balanced expression. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided bevelling at the edges ensures a classic, full plank look and feel. Every board is meticulously hand-scraped, which enhances the worn appearance of the floor.

PRODUCT DETAILS		PRODUCT DETAILS	
Product type / Construction	Wood Floors / 3-layer parquet	Hardness (Brinell) value /	3,7 / 2.2 - 5
Article Number / EAN Code	151NCSEK04KW240 / 7393969038997	range	
Design / Wood Species	1-strip / Oak	Warranty	30 years
Surface treatment /	Oil / Stained	TECHNICAL PROPERTIES	
Natural/Stained		Moisture content	EN13183
Design features	Bevelled 4-sided, Brushed, Light smoked,		LINIDIOD
	Handscraped	Minimun Mean Density — kg/m³	
Width x Length x Thickness	187 x 2420 x 15 mm	— Reaction To Fire	EN13501-1
Weight per package / per	22 kg / 8.15 kg	Formaldehyde Emission	EN717-1
m2		— Content PCP	CEN/TR148
Area per package / per	2.72 m ² / 122.4 m ²	-	EN1533
pallet		Breaking Strength N/mm²	
Grading	Dynamic	Thermal Conductivity	EN12664
Joint	Woodloc® 5S	Biological Durability	EN350-2
Installation method	Floating, Glue-down	— CARB2	
Floor heating	Yes	Slip resistance	CEN/TS156
Wear leayer material /	Hardwood / 3.5 mm	TSCA SONAN ECOL	MESSION CLASS
thickness		CARB P2	M1>
Resandable	2-4 times	Compliant	\$ SYAM ONIO
Core material	Pine/Spruce lamella	floor CC	

naruriess (Brirleii) value /	5,7 7 2.2 - 5.9	
range		
Warranty	30 years	
TECHNICAL PROPERTIES		
Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m³
kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 ppm
Breaking Strength N/mm ²	EN1533	NPD
Thermal Conductivity	EN12664	0,11W/mK
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CEN/TS15676	NPD













DETAILED DESCRIPTION

Backside material

All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur.

The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

Oil: This floor should be oiled immediately after installation.

Colour change: Stained product - noticable color change over time.

Packages may contain start and stop boards.

Descriptions & Imagery

Other products in this collection



OAK KLINTA



OAK SEVEDE



OAK YDRE



OAK MÖRE



OAK VISTA



OAK VEDBO



OAK TVETA



OAK FINNVEDEN



OAK ASPELAND