

## OAK SEVEDE

The subtle, amber stain on this single-strip oak floor from the Småland Collection allows the rich and warm tones in the wood to seep through, resulting in a lively expression and a naturally balanced contrast. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided bevelling at the edges ensures a classic, full plank look and feel. Every board is meticulously hand-scraped, which enhances the worn appearance of the floor.

PRODUCT DETAILS		PRODUCT DETAILS		
Product type / Construction	Wood Floors / 3-layer parquet	Hardness (Brinell) value /	3,7 / 2.2 - 5.9	
Article Number / EAN Code	151NCSEK05KW240 / 7393969039000	range		
Design / Wood Species	1-strip / Oak	Warranty	30 years	
Surface treatment /	Oil / Stained	TECHNICAL PROPERTIES	:	
Natural/Stained		— Moisture content	, FN13183	7%±2%
Design features	Bevelled 4-sided, Brushed, Light smoked,	Minimun Mean Density	LINISIOS	>500 kg/m <sup>3</sup>
	Handscraped	— kg/m <sup>3</sup>		>500 kg/11
Width x Length x Thickness	187 x 2420 x 15 mm	— Reaction To Fire	EN13501-1	Dfl-s1
Weight per package / per	22 kg / 8.15 kg	Formaldehyde Emission	EN717-1	F1
m2		Content PCP	CEN/TR14823	
Area per package / per	2.72 m <sup>2</sup> / 122.4 m <sup>2</sup>			≤ 5 ppm
pallet		Breaking Strength N/mm <sup>2</sup>	EN1533	NPD
Grading	Dynamic	Thermal Conductivity	EN12664	0,11W/mK
Joint	Woodloc® 5S	Biological Durability	EN350-2	Class 1
Installation method	Floating, Glue-down	CARB2		Compliant
Floor heating	Yes		CEN/TS15676	NPD
Wear leayer material /	Hardwood / 3.5 mm		à la	floor
thickness				A+ score
Resandable	2-4 times	Compliant SundaHus Asylyw ON	BASTA	Contraction of the services
Core material	Pine/Spruce lamella			((
Backside material	Veneer			して

## DETAILED DESCRIPTION

All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur.

The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

Oil: This floor should be oiled immediately after installation.

Colour change: Stained product - noticable color change over time.

Packages may contain start and stop boards.

## **Descriptions & Imagery**

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

## Other products in this collection





OAK SEVEDE





OAK YDRE





OAK MÖRE



OAK VEDBO

OAK TVETA

OAK FINNVEDEN



OAK ASPELAND

OAK KLINTA

OAK VISTA