



OAK SEVEDE

Rich and warm tones from amber provides natural contrast and liveliness. The scraped, 3 dimensional structure enhances the knots, giving the floor a worn look and feel.

PRODUCT DETAILS		
Product type / Construction	Wood Flooring / 3-layer parquet	
Article Number / EAN Code	151NCSEK05KW240 / 7393969039000	
Design / Wood Species	1-strip / Oak	
Surface Treatment /	Oil / Stained	
Natural/Stained		
Refining Treatment	Bevelled 4-sided, Brushed, Light smoked,	
	Handscraped	
Width x Length x Thickness	187 x 2420 x 15 mm	
Weight per package / per	22 kg / 8.15 kg	
m2		
Area per package / per	2.72 m ² / 122.4 m ²	
pallet		
Grading	Dynamic	
Joint	Woodloc® 5S	
Installation method	Floating, Glue-down	
Floor heating	Yes	
Wear leayer material /	Hardwood / 3.5 mm	
thickness		
Core material	Pine/Spruce	
Backside material	Veneer	
Hardness (Brinell) value /	3,7 / 2.2 - 5.9	
range		

PRODUCT DFTAII	ς

Warranty	30 years	
- TECHNICAL PROPERTIES	i	
- Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m³
- kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
- Content PCP	CEN/TR14823	≤ 5 x 10-6n
Breaking Strength N/mm ²	EN1533	NPD
Biological Durability	EN350-2	Class 1
CARB2		Compliant
- Slip resistance	CEN/TS15676	NPD









DETAILED DESCRIPTION

All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur.

The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

Oil: This floor should be oiled immediately after installation.

Colour change: Stained product - noticable color change over time.

Packages may contain start and stop boards.

Other products in this collection



OAK KLINTA



OAK SEVEDE



OAK YDRE



OAK MÖRE



OAK VISTA



OAK VEDBO



OAK TVETA



OAK FINNVEDEN



OAK ASPELAND