

# OAK SEVEDE

Rich and warm tones from amber provides natural contrast and liveliness. The scraped, 3 dimensional structure enhances the knots, giving the floor a worn look and feel.


PRODUCT DETAILS		PRODUCT DETAILS	
Product type / Construction	Wood Flooring / 3-layer parquet	Warranty	30 years
Article Number / EAN Code	151NCSEK05KW240 / 7393969039000	TECHNICAL PROPERTIES	
Design / Wood Species	1-strip / Oak	Moisture content	EN13183 7%±2%
Surface Treatment / Natural/Stained	Oil / Stained	Minimun Mean Density	>500 kg/m <sup>3</sup>
Refining Treatment	Bevelled 4-sided, Brushed, Light smoked, Handscraped	Reaction To Fire	EN13501-1 Dfl-s1
Width x Length x Thickness	187 x 2420 x 15 mm	Formaldehyde Emission	EN717-1 E1
Weight per package / per m2	22 kg / 8.15 kg	Content PCP	CEN/TR14823 ≤ 5 x 10-6n
Area per package / per pallet	2.72 m <sup>2</sup> / 122.4 m <sup>2</sup>	Breaking Strength N/mm <sup>2</sup>	EN1533 NPD
Grading	Dynamic	Thermal Resistance R-Value	.11 (m2K/W)
Joint	Woodloc® 5S	Biological Durability	EN350-2 Class 1
Installation method	Floating, Glue-down	CARB2	Compliant
Floor heating	Yes	Slip resistance	CEN/TS15676 NPD
Wear leayer material / thickness	Hardwood / 3.5 mm	   	
Core material	Pine/Spruce lamella		
Backside material	Veneer		
Hardness (Brinell) value / range	3,7 / 2.2 - 5.9		

## DETAILED DESCRIPTION


All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

- Oil:** This floor should be oiled immediately after installation.
- Colour change:** Stained product - noticable color change over time.
- Packages may contain start and stop boards.


## Other products in this collection



OAK KLINTA




OAK SEVEDE




OAK YDRE




OAK MÖRE




OAK VISTA



OAK VEDBO



OAK TVETA



OAK FINNVEDEN



OAK ASPELAND