



## OAK TVETA

PRODUCT DETAILS

The rich, coffee stain on this single-strip oak floor from the Småland Collection allows the fully smoked, charcoal nuances in the wood to seep through, resulting in a very rustic expression. Light and dark contrasts in the wood are punctuated with occasional saw marks, which give the floor its restored appearance. Four-sided bevelling at the edges ensures a classic, full plank look and feel. Each board is meticulously hand-scraped, which enhances the rustic appearance of the floor.

PRODUCT DETAILS		PI
Product type / Construction	Wood Floors / 3-layer parquet	Ha
Article Number / EAN Code	151NDSEK04KW240 / 7393969039055	ra
Design / Wood Species	1-strip / Oak	W
Surface treatment /	Oil / Stained	TE
Natural/Stained		— <u>II</u>
Design features	Bevelled 4-sided, Brushed, Light smoked,	
	Handscraped, Saw marks	
Width x Length x Thickness	187 x 2420 x 15 mm	— <u>kg</u> — Re
Weight per package / per	22 kg / 8.15 kg	FC
m2		— Co
Area per package / per	2.72 m <sup>2</sup> / 122.4 m <sup>2</sup>	Br
pallet		— <u>Di</u> — Th
Grading	Expressive	— <u>     </u>    Bi
Joint	Woodloc® 5S	— CA
Installation method	Floating, Glue-down	_
Floor heating	Yes	— <u>Sli</u>
Wear leayer material /	Hardwood / 3.5 mm	
thickness		
Resandable	2-4 times	
Core material	Pine/Spruce lamella	
Backside material	Veneer	

## PRODUCT DETAILS

Hardness (Brinell) value /	3,7 / 2.2 - 5.9	
range		
Warranty	30 years	
TECHNICAL PROPERTIES	5	
Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m³
kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 ppm
Breaking Strength N/mm²	EN1533	NPD
Thermal Conductivity	EN12664	0,11W/mK
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CEN/TS15676	NPD

















## **DETAILED DESCRIPTION**

All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur.

The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

Oil: This floor should be oiled immediately after installation.

**Colour change**: Stained product - noticable color change over time.

Packages may contain start and stop boards.

**Descriptions & Imagery** 

## Other products in this collection



OAK KLINTA



OAK SEVEDE



OAK YDRE



OAK MÖRE



OAK VISTA



OAK VEDBO



OAK TVETA



OAK FINNVEDEN



OAK ASPELAND