



## **TVETA**

DDODLICT DETAILS

PRODUCT DETAILS		
Product type / Construction	Wood Flooring / 3-layer engineered	
Article Number / EAN Code	151NDSEK04KW240 / 7393969039055	
Design / Wood Species	1-strip / White Oak	
Surface Treatment /	Oil / Stained	
Natural/Stained		
Refining Treatment	Beveled 4-sided, Brushed, Light smoked,	
	Handscraped, Saw marks	
Width x Length x Thickness	7 3/8 x 95 1/4 x 5/8"	
Weight per package / per	48.5 lbs / 18 lbs	
m2		
Area per package / per	29.1 sqft / 1317.5 sqft	
pallet		
Grading	Expressive	
Joint	Woodloc® 5S	
Installation method	Floating, Glue-Down	
Floor heating	Yes	
Wear leayer material /	Hardwood / 1/8"	
thickness		
Resandable	2 times	
Core material	Pine/Spruce lamella	
Backside material	Veneer	

## PRODUCT DETAILS

Hardness (Brinell) value /	3,7 / 2.2 - 5.9	
range		
TECHNICAL PROPERTIES	5	
Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m³
kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 x 10-6n
Breaking Strength N/mm <sup>2</sup>	EN1533	NPD
Thermal Resistance R-Value	2	.11 (m2K/W)
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CEN/TS15676	NPD









## DETAILED DESCRIPTION

All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur.

The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

Oil: This floor should be oiled immediately after installation.

**Colour change**: Stained product - noticable color change over time.

Packages may contain start and stop boards.

## Other products in this collection



Oak Klinta



Sevede



Ydre



Möre



Vista

Vedbo

Tveta



Finnveden



Aspeland