



# TVETA


PRODUCT DETAILS		FACTS		TECHNICAL PROPERTIES		
Article Number	151NDSEK04KW240	Wood Species	White Oak	Moisture	EN13183	7%±2%
EAN Code	7393969039055	Design	1-strip	content		
Surface Treatment	Oil This floor should be oiled immediately after installation.	Grading	Expressive	Minimun Mean Density kg/m³ >500 kg/m³		
		Range	Kährs Supreme	Reaction To Fire	EN13501-1	Dfl-s1
		Collection	Småland Collection	Formaldehyde	EN717-1	E1
Refining Treatment	Beveled 4-sided, Brushed, Light smoked, Handscraped, Saw marks	Resandable	2 times	Emission		
		Natural/Stained	Stained	Content PCP	CEN/TR14823	≤ 5 x 10-6n
Dimensions	7 3/8 x 95 1/4 "	Brinell Value	3,7	Breaking Strength N/mm²	EN1533	NPD
Weight per Package	48.5 lbs	Joint	Woodloc® 5S			
Area per Package	29.1 sqft	Floor heating	Yes	Thermal	EN12664	0,14 W/mK
Area per pallet	1317.5 sqft	Warranty	30 years	Conductivity		
Package info	Packages may contain start and stop boards.	Wear-layer material	Hardwood	Thermal Resistance R-Value		.11 (m2K/W)
		Wear Layer Thickness	1/8"	Biological Durability	EN350-2	Class 1
DETAIL DESCRIPTION		Core material	Pine/Spruce lamella	CARB2		Compliant
All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Knots and cracks will be		Backside material	Veneer	Slipperiness	CEN/TS15676	'
		Thickness	5/8"	Jiipperiiless	CEIW/1313070	IN D
		Installation method	Floating, Glue-Down			

#### **COLOR CHANGE**

present in all sizes and numbers.

Stained product - noticable color change over time.

## Other products in this collection



#### CERTIFICATES

Finnveden









Aspeland

## **Descriptions & Imagery**

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.