



OAK VEDBO

The warm golden stain on this single-strip oak floor from the Småland Collection enhances the late autumn harvest tones in the wood, resulting in a lively expression and naturally balanced contrast. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided bevelling at the edges ensures a classic, full plank look and feel. Every board is meticulously hand-scraped, which enhances the worn appearance of the floor.

PRODUCT DETAILS

| | |
|---------------------------|---|
| Article Number | 151NCSEK01KW240 |
| EAN Code | 7393969038966 |
| Surface treatment | Oil This floor should be oiled immediately after installation. |
| Design features | Bevelled 4-sided, Brushed, Handscraped |
| Dimensions | 187 x 2420 mm |
| Weight per Package | 22 kg |
| Area per Package | 2.7 m ² |
| Area per pallet | 122.4 m ² |
| Package info | Packages may contain start and stop boards. |

DETAIL DESCRIPTION

All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

COLOUR CHANGE

Some muting of colour variation to medium, straw brown.


FACTS

| | |
|-----------------------------|---------------------|
| Wood Species | Oak |
| Design | 1-strip |
| Grading | Dynamic |
| Range | Kährs Supreme |
| Collection | Småland Collection |
| Resandable | 2-4 times |
| Natural/Stained | Natural |
| Brinell Value | 3,7 |
| Joint | Woodloc® 5S |
| Floor heating | Yes |
| Warranty | 30 years |
| Wear-layer material | Hardwood |
| Wear Layer Thickness | 3.5 mm |
| Core material | Pine/Spruce lamella |
| Backside material | Veneer |
| Thickness | 15 mm |
| Installation method | Floating, Glue-down |
| Surface Colour | Warm natural |

TECHNICAL PROPERTIES

| | | |
|--|--------------------------|--------------------------|
| Moisture content | EN13183 | 7%±2% |
| Minimum Mean Density kg/m³ | >500 kg/m ³ | |
| Reaction To Fire | EN13501-1 | Dfl-s1 |
| Formaldehyde Emission | EN717-1 | E1 |
| Content PCP | CEN/TR14823 | ≤ 5 x 10 ⁻⁶ n |
| Breaking Strength N/mm² | EN1533 | NPD |
| Thermal Conductivity | EN12664 | 0,14 W/mK |
| Thermal Resistance R-Value | .11 (m ² K/W) | |
| Biological Durability | EN350-2 | Class 1 |
| CARB2 | Compliant | |
| Slipperiness | CEN/TS15676 | NPD |


Other products in this collection




Oak Klinta



Oak Kinda




Oak Sevede




Oak Ydre




Oak Möre




Oak Vista




Oak Vedbo



Oak Handbörd



Oak Tveta



Oak Finnveden



Oak Aspeland

CERTIFICATES



Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.