

VISTA

PRODUCT DETAILS

PRODUCT DETAILS			TECHNICAL PROPERTIES
Product type / Construction	Wood Flooring / 3-layer engineered		Minimun Mean Density
Article Number / EAN Code	151NCSEK02KW240 / 7393969038973		kg/m ³
Design / Wood Species	1-strip / White Oak		Reaction To Fire
Surface Treatment /	Oil / Stained		Formaldehyde Emission
Natural/Stained			Content PCP
Refining Treatment	Beveled 4-sided, Brushed, Handscraped		Breaking Strength N/mm ²
Width x Length x Thickness	7 3/8 x 95 1/4 x 5/8"		Biological Durability
Weight per package / per	48.5 lbs / 18 lbs		CARB2
m2			Slip resistance
Area per package / per	29.3 sqft / 1317.5	sqft	
pallet			
Joint	Woodloc® 5S Floating, Glue-Down		Compliant
Installation method			
Floor heating	Yes		
Wear leayer material /	Hardwood / 1/8"		
thickness			
Resandable	2 times		_
Hardness (Brinell) value /	3,7 / 2.2 - 5.9		
range			
TECHNICAL PROPERTIES			
Moisture content	EN13183	7%±2%	

DETAILED DESCRIPTION

All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur.

The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

Oil: This floor should be oiled immediately after installation.

Colour change: Stained product - noticable color change over time.

Packages may contain start and stop boards.

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

Kährs International | www.kahrs.com | [©]Kährs, USA & Canada 2025-09-01

>500 kg/m³

≤ 5 x 10-6n

Dfl-s1

E1

NPD

Class 1 Compliant NPD

EN13501-1

CEN/TR14823

CEN/TS15676

EN717-1

EN1533

EN350-2

Other products in this collection













Möre



Vista



Tveta

eta

Finnveden



Aspeland