

## OAK ASPELAND

This flour-white stained, single-strip oak floor from the Småland Collection has an exceptionally rustic expression, balanced by its bisque finish. Light and dark contrasts in the wood are punctuated with occasional saw marks, which give the floor its restored appearance. Four-sided bevelling at the edges ensures a classic, full plank look and feel. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood.

PRODUCT DETAILS		PRODUCT DETAILS		
Product type / Construction	Wood Floors / 3-layer parquet	Hardness (Brinell) value /	3,7 / 2.2 - 5.9	
Article Number / EAN Code	151NDSEK01KW240 / 7393969039024	range		
Design / Wood Species	1-strip / Oak	Warranty	30 years	
Surface treatment /	Oil / Stained	TECHNICAL PROPERTIES		
Natural/Stained		- Moisture content	EN13183	7%±2%
Design features	Bevelled 4-sided, Brushed, Handscraped, Saw marks	Minimun Mean Density	LINISTOS	>500 kg/m <sup>3</sup>
Width x Length x Thickness	187 x 2420 x 15 mm	- <u>kg</u> /m³ - Reaction To Fire	EN13501-1	Dfl-s1
Weight per package / per	22 kg / 8.15 kg	Formaldehyde Emission	EN717-1	E1
m2	272 244224 2	Content PCP	CEN/TR14823	≤ 5 ppm
Area per package / per	2.72 m <sup>2</sup> / 122.4 m <sup>2</sup>	Breaking Strength N/mm <sup>2</sup>	EN1533	NPD
pallet		- Thermal Conductivity	EN12664	0,11W/mK
Grading	Expressive	Biological Durability	EN350-2	Class 1
Joint	Woodloc® 5S	- CARB2		Compliant
Installation method	Floating, Glue-down	- Slip resistance	CEN/TS15676	NPD
Floor heating	Yes		CENTSTSOTO	
Wear leayer material /	Hardwood / 3.5 mm			HIGHLAND HIGHLAND FIGURE
thickness			BASTA	A+ score
Resandable	2-4 times	Compliant SundaHus	DAJIA	SSCS Global Services
Core material	Pine/Spruce lamella	-		((
Backside material	Veneer	-		して

## DETAILED DESCRIPTION

All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur.

The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

Oil: This floor should be oiled immediately after installation.

Colour change: Stained product - noticable color change over time.

Packages may contain start and stop boards.

## **Descriptions & Imagery**

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

## Other products in this collection





OAK SEVEDE





OAK YDRE





OAK MÖRE



OAK VEDBO

OAK TVETA

OAK FINNVEDEN



OAK ASPELAND

OAK KLINTA

OAK VISTA