



## OAK ASPELAND

Wear and tear with light colors from bread and flour. Aspeland is an extremely rustic board with knots and cracks giving it an old, restored look.

PRODUCT DETAILS		
Product type / Construction	Wood Flooring / 3-layer parquet	
Article Number / EAN Code	151NDSEK01KW240 / 7393969039024	
Design / Wood Species	1-strip / Oak	
Surface Treatment /	Oil / Stained	
Natural/Stained		
Refining Treatment	Bevelled 4-sided, Brushed, Handscraped, Saw	
	marks	
Width x Length x Thickness	187 x 2420 x 15 mm	
Weight per package / per	22 kg / 8.15 kg	
m2		
Area per package / per	2.72 m <sup>2</sup> / 122.4 m <sup>2</sup>	
pallet		
Grading	Expressive	
Joint	Woodloc® 5S	
Installation method	Floating, Glue-down	
Floor heating	Yes	
Wear leayer material /	Hardwood / 3.5 mm	
thickness		
Core material	Pine/Spruce	
Backside material	Veneer	
Hardness (Brinell) value /	3,7 / 2.2 - 5.9	
range		

<b>PROD</b>	UCT	DETAI	LS
-------------	-----	-------	----

Warranty	30 years	
TECHNICAL PROPERTIES	5	
Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m³
kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 x 10-6n
Breaking Strength N/mm²	EN1533	NPD
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CEN/TS15676	NPD









## DETAILED DESCRIPTION

All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur.

The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

Oil: This floor should be oiled immediately after installation.

**Colour change**: Stained product - noticable color change over time.

Packages may contain start and stop boards.

## Other products in this collection



OAK KLINTA



OAK SEVEDE



OAK YDRE



OAK MÖRE



OAK VISTA



OAK VEDBO



OAK TVETA



OAK FINNVEDEN



OAK ASPELAND