



Småland Collection



OAK ASPELAND

This flour-white stained, single-strip oak floor from the Småland Collection has an exceptionally rustic expression, balanced by its bisque finish. Light and dark contrasts in the wood are punctuated with occasional saw marks, which give the floor its restored appearance. Four-sided bevelling at the edges ensures a classic, full plank look and feel. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood.

PRODUCT DETAILS

| | |
|-------------------------------------|--|
| Product type / Construction | Wood Flooring / 3-layer engineered |
| Article Number / EAN Code | 151NDSEK01KW240 / 7393969039024 |
| Design / Wood Species | Plank / White Oak |
| Surface Treatment / Natural/Stained | Oil / Stained |
| Refining Treatment | Beveled 4-sided, Brushed, Handscraped, Saw marks |
| Width x Length x Thickness | 7 3/8 x 95 1/4 x 5/8" |
| Weight per package / per m2 | 48.5 lbs / 18 lbs |
| Area per package / per pallet | 29.3 sqft / 1317.5 sqft |
| Grading | Expressive |
| Joint | Woodloc® 5S |
| Installation method | Floating, Glue-Down |
| Floor heating | Yes |
| Wear layer material / thickness | Hardwood / 1/8" |
| Resandable | 2 times |
| Core material | Pine/Spruce |
| Backside material | Veneer |

PRODUCT DETAILS

| | |
|----------------------------------|-----------------|
| Hardness (Brinell) value / range | 3,7 / 2.2 - 5.9 |
|----------------------------------|-----------------|

TECHNICAL PROPERTIES

| | | |
|--|-------------|------------------------|
| Moisture content | EN13183 | 7%±2% |
| Minimun Mean Density kg/m ³ | | >500 kg/m ³ |
| Reaction To Fire | EN13501-1 | Dfl-s1 |
| Formaldehyde Emission | EN717-1 | E1 |
| Content PCP | CEN/TR14823 | ≤ 5 x 10-6n |
| Breaking Strength N/mm ² | EN1533 | NPD |
| Biological Durability | EN350-2 | Class 1 |
| CARB2 | | Compliant |
| Slip resistance | CEN/TS15676 | NPD |



DETAILED DESCRIPTION

All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur.

The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

Oil: This floor should be oiled immediately after installation.

Colour change: Stained product - noticeable color change over time.

Packages may contain start and stop boards.

Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

Kährs International |
www.kahr.com | ©Kährs,
USA & Canada 2026-03-13

Other products in this collection



OAK KLINTA



OAK SEVEDE



OAK YDRE



OAK MÖRE



OAK VISTA



OAK VEDBO



OAK TVETA



OAK FINNVEDEN



OAK ASPELAND