



OAK MÖRE

DDODLICT DETAILS

A rustic product with a scraped, flowing surface that high enhances the structure in an natural way. The cold greys appear to have been worn down, revealing a warmer base.

Wood Flooring / 3-layer parquet
151NCSEK03KW240 / 7393969038980
1-strip / Oak
Oil / Stained
Bevelled 4-sided, Brushed, Handscraped
187 x 2420 x 15 mm
22 kg / 8.15 kg
2.72 m ² / 122.4 m ²
Dynamic
Woodloc® 5S
Floating, Glue-down
Yes
Hardwood / 3.5 mm
Pine/Spruce
Veneer
3,7 / 2.2 - 5.9

PRODUCT DETAILS		
Warranty	30 years	
TECHNICAL PROPERTIES	S	
Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m³
kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 x 10-6n
Breaking Strength N/mm ²	EN1533	NPD
Biological Durability	EN350-2	Class 1
CARB2		Compliant
Slip resistance	CEN/TS15676	NPD









DETAILED DESCRIPTION

All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur.

The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

Oil: This floor should be oiled immediately after installation.

Colour change: Stained product - noticable color change over time.

Packages may contain start and stop boards.

Other products in this collection



OAK KLINTA



OAK SEVEDE



OAK YDRE



OAK MÖRE



OAK VISTA



OAK VEDBO



OAK TVETA



OAK FINNVEDEN



OAK ASPELAND