



## OAK MÖRE

A rustic product with a scraped, flowing surface that high enhances the structure in an natural way. The cold greys appear to have been worn down, revealing

PRODUCT DETAILS		PRODUCT DETAILS
Product type / Construction	Wood Flooring / 3-layer parquet	Warranty
Article Number / EAN Code	151NCSEK03KW240 / 7393969038980	— TECHNICAL PROPER
Design / Wood Species	1-strip / Oak	Moisture content
Surface Treatment /	Oil / Stained	
Natural/Stained		Minimun Mean Density
Refining Treatment	Bevelled 4-sided, Brushed, Handscraped	— kg/m³
Width x Length x Thickness	187 x 2420 x 15 mm	Reaction To Fire
Weight per package / per	22 kg / 8.15 kg	Formaldehyde Emissio
m2		Content PCP
Area per package / per	2.72 m <sup>2</sup> / 122.4 m <sup>2</sup>	Breaking Strength N/m
pallet		Biological Durability
Grading	Dynamic	CARB2
Joint	Woodloc® 5S	Slip resistance
Installation method	Floating, Glue-down	ugsion ccas
Floor heating	Yes	M1) A+
Wear leayer material /	Hardwood / 3.5 mm	- ASTAM ONIG
thickness		
Core material	Pine/Spruce	
Backside material	Veneer	
Hardness (Brinell) value /	3,7 / 2.2 - 5.9	
range		

Warranty	30 years	
TECHNICAL PROPERTIES		
Moisture content	EN13183	7%±2%
Minimun Mean Density		>500 kg/m³
kg/m³		
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 x 10-6n
Breaking Strength N/mm²	EN1533	NPD
Biological Durability	EN350-2	Class 1









CEN/TS15676

## DETAILED DESCRIPTION

All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur.

The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

**Oil:** This floor should be oiled immediately after installation.

Colour change: Stained product - noticable color change over time.

Packages may contain start and stop boards.

Compliant NPD

## Other products in this collection



OAK KLINTA



OAK SEVEDE



OAK YDRE



OAK MÖRE



OAK VISTA



OAK VEDBO



OAK TVETA



OAK FINNVEDEN



OAK ASPELAND