



OAK MÖRE

DDODLICT DETAILS

The even grey stain on this single-strip oak floor from the Småland Collection allows the warmer nuances in the wood to seep through, resulting in a calm and balanced expression. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided bevelling at the edges ensures a classic, full plank look and feel. Every board is meticulously hand-scraped, which enhances the rustic appearance of the floor.

| PRODUCT DETAILS | |
|-----------------------------|---------------------------------------|
| Product type / Construction | Wood Flooring / 3-layer engineered |
| Article Number / EAN Code | 151NCSEK03KW240 / 7393969038980 |
| Design / Wood Species | 1-strip / White Oak |
| Surface Treatment / | Oil / Stained |
| Natural/Stained | |
| Refining Treatment | Beveled 4-sided, Brushed, Handscraped |
| Width x Length x Thickness | 7 3/8 x 95 1/4 x 5/8" |
| Weight per package / per | 48.5 lbs / 18 lbs |
| m2 | |
| Area per package / per | 29.3 sqft / 1317.5 sqft |
| pallet | |
| Grading | Dynamic |
| Joint | Woodloc® 5S |
| Installation method | Floating, Glue-Down |
| Floor heating | Yes |
| Wear leayer material / | Hardwood / 1/8" |
| thickness | |
| Resandable | 2 times |
| Core material | Pine/Spruce |
| Backside material | Veneer |
| | |

| ٢ | K | U | D | U | C | l | U | E | l P | ۱I | LS |
|---|---|---|---|---|---|---|---|---|-----|----|----|
| | | | | | | | | | | | |

3,7 / 2.2 - 5.9 Hardness (Brinell) value / range

| TECHNICAL PROPERTIES | 5 | | | |
|-------------------------|-------------|-------------|--|--|
| Moisture content | EN13183 | 7%±2% | | |
| Minimun Mean Density | | >500 kg/m³ | | |
| kg/m³ | | | | |
| Reaction To Fire | EN13501-1 | Dfl-s1 | | |
| Formaldehyde Emission | EN717-1 | E1 | | |
| Content PCP | CEN/TR14823 | ≤ 5 x 10-6n | | |
| Breaking Strength N/mm² | EN1533 | NPD | | |
| Biological Durability | EN350-2 | Class 1 | | |
| CARB2 | | Compliant | | |
| Slip resistance | CEN/TS15676 | NPD | | |











DETAILED DESCRIPTION

All naturally occuring wood colour variations allowed, from light to dark brown. Sapwood may occur.

The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

Oil: This floor should be oiled immediately after installation.

Colour change: Stained product - noticable color change over time.

Packages may contain start and stop boards.

Other products in this collection



OAK KLINTA

OAK VISTA



OAK SEVEDE



OAK YDRE



OAK MÖRE





OAK VEDBO



OAK TVETA



OAK FINNVEDEN



OAK ASPELAND