



## TONGASS DBW 229-055 - 0.55 MM

Our Luxury Tiles Dry Back collection is available in a wide selection of wood and stone designs. The wood designs range from traditional to rustic, while the stone designs span from classic stone to concrete. It also includes exciting patterns. The Dry Back floors, with a 0.55 mm wear layer, are based on virgin vinyl and constructed in five different layers, topped by a ceramic coating. The result is extremely resilient and strong floors resistant to both scratching and water, which means that these floors are suitable even for spaces exposed to heavy traffic. Just like all our other Luxury Tiles floors, they are phthalate-free.

PRODUCT DETAILS		
Product type / Construction	Luxury Vinyl Tiles and Planks / Dry Back LVT	
Article Number / EAN Code	LTDBW2006-229-5 / 7393969113489	
Design	Tile Design	
Width x Length x Thickness	229 x 1219 x 2.5 mm	
Weight per package / per	16 kg / 4 kg	
m2		
Area per package / per	3.9 m <sup>2</sup> / 265.6 m <sup>2</sup>	
pallet		
Installation method	Glue-down	
Floor heating	Yes	
Wear leayer thickness	0.55 mm	
TECHNICAL PROPERTIES		
Reaction To Fire	EN13501-1	Bfl-s1
Thermal Resistance R-Value		0.011 (m2K/W)
Dimensional stability	EN ISO 23999	< 0.1 %
Colour fastness	EN ISO 105-B02	≥ 6
Slip resistance	EN 13893	DS (>0.3)

DIN 51130

Statical electrical	EN 1815	< 2 kV
propensity		

V (antistatic) Chemical resistance EN ISO 26987 Pass with good results Suitable Effect of castor chair EN 425 Resistance to bacteria and Good fungi





**TECHNICAL PROPERTIES** 

**Descriptions & Imagery** 

Slip resistance

R10

## Other products in this collection





HUMBOLDT - DRY BACK

PLITVICE - DRY BACK

TRIGLAV - DRY BACK