



TAIGA DBW 229-055 - 0.55 MM

Our Luxury Tiles Dry Back collection is available in a wide selection of wood and stone designs. The wood designs range from traditional to rustic, while the stone designs span from classic stone to concrete. It also includes exciting patterns. The Dry Back floors, with a 0.55 mm wear layer, are based on virgin vinyl and constructed in five different layers, topped by a ceramic coating. The result is extremely resilient and strong floors resistant to both scratching and water, which means that these floors are suitable even for spaces exposed to heavy traffic. Just like all our other Luxury Tiles floors, they are phthalate-free.

| PRODUCT DETAILS | | | TECHNIC | CAL PROPERTIES |
|-----------------------------|--|---------------|----------------------------|--|
| Product type / Construction | Luxury Vinyl Tiles and Planks / Dry Back LVT | | Statical electrical | |
| Article Number / EAN Code | LTDBW2115-229-5 / 7393969113632 | | propensity | |
| Design | Tile Design | | Chemical | resistance |
| Width x Length x Thickness | 229 x 1219 x 2.5 mm | | Effect of castor chair | |
| Weight per package / per | 16 kg / 4 kg | | Resistance to bacteria and | |
| m2 | | | fungi | |
| Area per package / per | 4 m ² / 265.6 m ² | | SEION CLAS | The state of the s |
| pallet | | | _ :M1>: | floor score |
| Installation method | Glue-down | | A STAN ON OFFICE | O SCS Gishal Services |
| Floor heating | Yes | | <u>_</u> | |
| Wear leayer thickness | 0.55 mm | | _ | |
| TECHNICAL PROPERTIES | | | _ | |
| Reaction To Fire | EN13501-1 | Bfl-s1 | _ | |
| Thermal Resistance R-Value | | 0.011 (m2K/W) | _ | |
| Dimensional stability | EN ISO 23999 | < 0.1 % | _ | |
| Colour fastness | EN ISO 105-B02 | ≥ 6 | <u></u> | |
| Slip resistance | EN 13893 | DS (>0.3) | _ | |

DIN 51130

| Statical electrical | EN 1815 | < 2 kV (antistatic) |
|----------------------------|--------------|------------------------|
| propensity | | |
| Chemical resistance | EN ISO 26987 | Pass with good results |
| Effect of castor chair | EN 425 | Suitable |
| Resistance to bacteria and | | Good |
| fungi | | |





Descriptions & Imagery

Slip resistance

R10

Other products in this collection





HUMBOLDT - DRY BACK

PLITVICE - DRY BACK

TRIGLAV - DRY BACK