



< 2 kV (antistatic)

Suitable

Good

Pass with good results

TAIGA DBW 229-055 - 0.55 MM

Our Luxury Tiles Dry Back collection is available in a wide selection of wood and stone designs. The wood designs range from traditional to rustic, while the stone designs span from classic stone to concrete. It also includes exciting patterns. The Dry Back floors, with a 0.55 mm wear layer, are based on virgin vinyl and constructed in five different layers, topped by a ceramic coating. The result is extremely resilient and strong floors resistant to both scratching and water, which means that these floors are suitable even for spaces exposed to heavy traffic. Just like all our other Luxury Tiles floors, they are phthalate-free.

PRODUCT DETAILS			TECHNIC	CAL PROPERTIES
Product type / Construction	Vinyl Flooring / Dry Back LVT		Statical electrical	
Article Number / EAN Code	LTDBW2115-229-5 / 7393969113632		propensity	
Design	Tile Design		Chemical resistance	
Width x Length x Thickness	9 x 48 x 1/8"		Effect of castor chair	
Weight per package / per	35.3 lbs / 8.8 lbs		Resistance to bacteria and	
m2			fungi	
Area per package / per	43.1 sqft / 2858.9 sqft		SION C/	The state of the s
pallet			_ *M1>:	floor score
Installation method	Glue-Down		TAN ONIGH	O SCS Glabal Services
Floor heating	Yes		_	
Wear leayer thickness	0"		_	
TECHNICAL PROPERTIES			_	
Reaction To Fire	EN13501-1	Bfl-s1	_	
Thermal Resistance R-Value		0.011 (m2K/W)	_	
Dimensional stability	EN ISO 23999	< 0.1 %	_	
Colour fastness	EN ISO 105-B02	≥ 6	_	
Slip resistance	EN 13893	DS (>0.3)	_	

DIN 51130





EN 1815

EN 425

EN ISO 26987

Slip resistance

DDODLIGT DETAIL O

R10

Other products in this collection





Triglav - Dry back