



< 2 kV (antistatic)

Suitable

Good

Pass with good results

EN 1815

EN 425

EN ISO 26987

BELLUNO DBW 229-055 - 0.55 MM

Our Luxury Tiles Dry Back collection is available in a wide selection of wood and stone designs. The wood designs range from traditional to rustic, while the stone designs span from classic stone to concrete. It also includes exciting patterns. The Dry Back floors, with a 0.55 mm wear layer, are based on virgin vinyl and constructed in five different layers, topped by a ceramic coating. The result is extremely resilient and strong floors resistant to both scratching and water, which means that these floors are suitable even for spaces exposed to heavy traffic. Just like all our other Luxury Tiles floors, they are phthalate-free.

PRODUCT DETAILS			TECHNICAL PROPERTIES
Product type / Construction	Luxury Vinyl Tiles and Planks / Dry Back LVT		Statical electrical
Article Number / EAN Code	LTDBW2111-229-5 / 7393969113601		propensity
Design	Plank		Chemical resistance
Width x Length x Thickness	229 x 1219 x 2.5 mm		Effect of castor chair
Weight per package / per	16 kg / 4 kg		Resistance to bacteria and
m2			fungi
Area per package / per	3.9 m ² / 265.2 m ²		
pallet			
Installation method	Glue-down		
Floor heating	Yes		
Wear leayer thickness	0.55 mm		_
TECHNICAL PROPERTIES			_
Reaction To Fire	EN13501-1	Bfl-s1	_
Thermal Resistance R-Value		0.011 (m2K/W)	
Dimensional stability	EN ISO 23999	< 0.1 %	<u>—</u>
Colour fastness	EN ISO 105-B02	≥ 6	<u>—</u>
Slip resistance	EN 13893	DS (>0.3)	
Slip resistance	DIN 51130	R10	

Other products in this collection





HUMBOLDT - DRY BACK

PLITVICE - DRY BACK

TRIGLAV - DRY BACK