



## KEBNEKAISE DRY BACK 0.55 MM

Our Luxury Tiles Dry Back collection is available in a wide selection of stone designs, spanning from classic stone to concrete. The Dry Back floors, with a 0.55 mm wear layer, are based on virgin vinyl and constructed in five different layers, topped by a ceramic coating. The result is extremely resilient and strong floors resistant to both scratching and water, which means that these floors are suitable even for spaces exposed to heavy traffic. Just like all our other Luxury Tiles floors, they are phthalate-free.

### PRODUCT DETAILS

|   |  |
|---|--|
| Product type / Construction             | Luxury Vinyl Tiles and Planks / Dry Back LVT |
| Article Number / EAN Code               | LTDBS3005-457-5 / 7393969113359              |
| Design                                  | Tile Design                                  |
| Width x Length x Thickness              | 457 x 457 x 2.5 mm                           |
| Weight per package / per m <sup>2</sup> | 21 kg / 4.2 kg                               |
| Area per package / per pallet           | 5.01 m <sup>2</sup> / 240.5 m <sup>2</sup>   |
| Installation method                     | Glue-down                                    |
| Floor heating                           | Yes  |
| Wear layer thickness                    | 0.55 mm                                      |

### TECHNICAL PROPERTIES

|                            |                |                            |
|----------------------------|----------------|----------------------------|
| Reaction To Fire           | EN13501-1      | Bfl-s1                     |
| Thermal Resistance R-Value |                | 0.011 (m <sup>2</sup> K/W) |
| Dimensional stability      | EN ISO 23999   | < 0.1 %                    |
| Colour fastness            | EN ISO 105-B02 | ≥ 6                        |
| Slip resistance            | EN 13893       | DS (>0.3)                  |
| Slip resistance            | DIN 51130      | R10                        |

### TECHNICAL PROPERTIES

|                                  |              |                        |
|----------------------------------|--------------|------------------------|
| Statical electrical propensity   | EN 1815      | < 2 kV (antistatic)    |
| Chemical resistance              | EN ISO 26987 | Pass with good results |
| Effect of castor chair           | EN 425       | Suitable               |
| Resistance to bacteria and fungi |              | Good                   |



### Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

Other products in this collection



KILIMANJARO DRY BACK



STEELE DRY BACK



SCHWARZHORN DRY BACK



MATTERHORN DRY BACK



MAKALU DRY BACK



LUCANIA DRY BACK



KEBNEKAISE DRY BACK



GROSSGLOCKNER DRY BACK



MONT BLANC DRY BACK



DOM DRY BACK



BROAD PEAK DRY BACK



LHOTSE DRY BACK