



## KEBNEKAISE DRY BACK 0.55 MM

Our Luxury Tiles Dry Back collection is available in a wide selection of wood and stone designs. The wood designs range from traditional to rustic, while the stone designs span from classic stone to concrete. It also includes exciting patterns. The Dry Back floors, with a 0.55 mm wear layer, are based on virgin vinyl and constructed in five different layers, topped by a ceramic coating. The result is extremely resilient and strong floors resistant to both scratching and water, which means that these floors are suitable even for spaces exposed to heavy traffic. Just like all our other Luxury Tiles floors, they are phthalate-free.

PRODUCT DETAILS			
Product type / Construction	Luxury Vinyl Tiles and Planks / Dry Back LVT		
Article Number / EAN Code	LTDBS3005-457-5 / 7393969113359		
Design	Tile Design		
Width x Length x Thickness	457 x 457 x 2.5 mm		
Weight per package / per	21 kg / 4.2 kg		
m2			
Area per package / per	5.01 m <sup>2</sup> / 240.5 m <sup>2</sup>		
pallet			
Installation method	Glue-down		
Floor heating	Yes		
Wear leayer thickness	0.55 mm		
TECHNICAL PROPERTIES			
Reaction To Fire	EN13501-1	Bfl-s1	
Thermal Resistance R-Value		0.011 (m2K/W)	
Dimensional stability	EN ISO 23999	< 0.1 %	
Colour fastness	EN ISO 105-B02	≥ 6	
Slip resistance	EN 13893	DS (>0.3)	

DIN 51130

T	ECI	HNI	CAL	PROP	ERTIES	)

Statical electrical	EN 1815	< 2 kV (antistatic)
propensity		
Chemical resistance	EN ISO 26987	Pass with good results
Resistance to bacteria and		Good
fungi		





Slip resistance

R10

## Other products in this collection

