



KEBNEKAISE DRY BACK 0.55 MM

Our Luxury Tiles Dry Back collection is available in a wide selection of wood and stone designs. The wood designs range from traditional to rustic, while the stone designs span from classic stone to concrete. It also includes exciting patterns. The Dry Back floors, with a 0.55 mm wear layer, are based on virgin vinyl and constructed in five different layers, topped by a ceramic coating. The result is extremely resilient and strong floors resistant to both scratching and water, which means that these floors are suitable even for spaces exposed to heavy traffic. Just like all our other Luxury Tiles floors, they are phthalate-free.

PRODUCT DETAILS		
Product type / Construction	Luxury Vinyl Tiles and Planks / Dry Back LVT	
Article Number / EAN Code	LTDBS3005-457-5 / 7393969113359	
Design	Tile Design	
Width x Length x Thickness	457 x 457 x 2.5 mm	
Weight per package / per	21 kg / 4.2 kg	
m2		
Area per package / per	5.01 m ² / 240.5 m ²	
pallet		
Installation method	Glue-down	
Floor heating	Yes	
Wear leayer thickness	0.55 mm	
TECHNICAL PROPERTIES		
Reaction To Fire	EN13501-1	Bfl-s1
Thermal Resistance R-Value		0.011 (m2K/W)
Dimensional stability	EN ISO 23999	< 0.1 %
Colour fastness	EN ISO 105-B02	≥ 6
Slip resistance	EN 13893	DS (>0.3)

DIN 51130

TECHNICAL PROPERTIES		
Statical electrical	EN 1815	< 2 kV (antistatic)
propensity		

Chemical resistance EN ISO 26987 Pass with good results
Resistance to bacteria and Good



fungi



Slip resistance

R10

Other products in this collection

