



SCHWARZHORN DRY BACK 0.55 MM

Our Luxury Tiles Dry Back collection is available in a wide selection of wood and stone designs. The wood designs range from traditional to rustic, while the stone designs span from classic stone to concrete. It also includes exciting patterns. The Dry Back floors, with a 0.55 mm wear layer, are based on virgin vinyl and constructed in five different layers, topped by a ceramic coating. The result is extremely resilient and strong floors resistant to both scratching and water, which means that these floors are suitable even for spaces exposed to heavy traffic. Just like all our other Luxury Tiles floors, they are phthalate-free.

PRODUCT DETAILS		TECHNICAL PROPERTIES		
Product type / Construction	Vinyl Flooring / Dry Back LVT	Statcal electrical	EN 1815	< 2 kV (antistatic)
Article Number / EAN Code	LTDBS3008-305-5 / 7393969113397	propensity		
Design	Tile Design	Chemical resistance	EN ISO 26987	Pass with good results
Width x Length x Thickness	24 x 12 x 1/8"	Effect of castor chair	EN 425	Suitable
Weight per package / per m2	24.3 lbs / 9.3 lbs	Resistance to bacteria and fungi		Good
Area per package / per pallet	27.8 sqft / 2998.8 sqft			
Installation method	Glue-Down			
Floor heating	Yes			
Wear leayer thickness	0"			
TECHNICAL PROPERTIES				
Reaction To Fire	EN13501-1	Bfl-s1		
Thermal Resistance R-Value		0.011 (m2K/W)		
Dimensional stability	EN ISO 23999	< 0.1 %		
Colour fastness	EN ISO 105-B02	≥ 6		
Slip resistance	EN 13893	DS (>0.3)		
Slip resistance	DIN 51130	R10		



Other products in this collection



KILIMANJARO DRY BACK



STEELE DRY BACK



SCHWARZHORN DRY BACK



MATTERHORN DRY BACK



MAKALU DRY BACK



LUCANIA DRY BACK



KEBNEKAISE DRY BACK



GROSSGLOCKNER DRY BACK



DOM DRY BACK



BROAD PEAK DRY BACK



LHOTSE DRY BACK