






Dry Back Stone Collection



LHOTSE DRY BACK 0.55 MM

Our Luxury Tiles Dry Back collection is available in a wide selection of stone designs, spanning from classic stone to concrete. The Dry Back floors, with a 0.55 mm wear layer, are based on virgin vinyl and constructed in five different layers, topped by a ceramic coating. The result is extremely resilient and strong floors resistant to both scratching and water, which means that these floors are suitable even for spaces exposed to heavy traffic. Just like all our other Luxury Tiles floors, they are phthalate-free.

PRODUCT DETAILS			TECHNICAL PROPERTIES		
Product type / Construction	Luxury Vinyl Tiles and Planks / Dry Back LVT		Statcal electrical	EN 1815	< 2 kV (antistatic)
Article Number / EAN Code	LTDBS3010-457-5 / 7393969113403		propensity		
Design	Tile Design		Chemical resistance	EN ISO 26987	Pass with good results
Width x Length x Thickness	457 x 457 x 2.5 mm		Effect of castor chair	EN 425	Suitable
Weight per package / per m2	21 kg / 4.2 kg		Resistance to bacteria and fungi		Good
Area per package / per pallet	5.01 m ² / 240.5 m ²		<div></div>		
Installation method	Glue-down				
Floor heating	Yes				
Wear leayer thickness	0.55 mm				
TECHNICAL PROPERTIES					
Reaction To Fire	EN13501-1	Bfl-s1			
Thermal Resistance R-Value		0.011 (m2K/W)			
Dimensional stability	EN ISO 23999	< 0.1 %			
Colour fastness	EN ISO 105-B02	≥ 6			
Slip resistance	EN 13893	DS (>0.3)			
Slip resistance	DIN 51130	R10			

Other products in this collection



KILIMANJARO DRY BACK



STEELE DRY BACK



SCHWARZHORN DRY BACK



MATTERHORN DRY BACK



MAKALU DRY BACK



LUCANIA DRY BACK




KEBNEKAISE DRY BACK



GROSSGLOCKNER DRY BACK




MONT BLANC DRY BACK



DOM DRY BACK



BROAD PEAK DRY BACK



LHOTSE DRY BACK