



LHOTSE DRY BACK 0.55 MM

Our Dry Back collection is available in a wide selection of wood and stone designs. The wood designs range from traditional to elegant herringbone and rustic, while the stone designs span from classic stone to concrete. It also includes exciting patterns. The Dry Back floors, with a 0.7 mm wear layer, are based on virgin vinyl and constructed in five different layers, topped by a ceramic coating. The result is extremely resilient and strong floors resistant to both scratching and water, which means that these floors are suitable even for spaces exposed to heavy traffic. Just like all our other Luxury Vinyl Plank floors, they are phthalate-free.

PRODUCT DETAILS		
Product type / Construction	Vinyl Flooring / Dry Back LVT	
Article Number / EAN Code	LTDBS3010-457-5 / 7393969113403	
Design	Tile Design	
Width x Length x Thickness	18 x 18 x 1/8"	
Weight per package / per	46.3 lbs / 9.3 lbs	
m2		
Area per package / per	53.9 sqft / 2588.7 sqft	
pallet		
Installation method	Glue-Down	
Floor heating	Yes	
Wear leayer thickness	0"	
TECHNICAL PROPERTIES		
Reaction To Fire	EN13501-1	Bfl-s1
Thermal Resistance R-Value		0.011 (m2K/W)

Floor heating	Yes	
Wear leayer thickness	0"	
TECHNICAL PROPERTIES		
Reaction To Fire	EN13501-1	Bfl-s1
Thermal Resistance R-Value		0.011 (m2K/W)
Dimensional stability	EN ISO 23999	< 0.1 %
Colour fastness	EN ISO 105-B02	≥ 6

EN 13893

DIN 51130

Statical electrical	EN 1815	< 2 kV (antistatic)
propensity		
Chemical resistance	EN ISO 26987	Pass with good results
Effect of castor chair	EN 425	Suitable
Resistance to bacteria and		Good
fungi		





TECHNICAL PROPERTIES

Statical electrical

Slip resistance

Slip resistance

DS (>0.3)

R10

Other products in this collection

