



MONT BLANC DRY BACK 0.55 MM

Our Luxury Tiles Dry Back collection is available in a wide selection of wood and stone designs. The wood designs range from traditional to rustic, while the stone designs span from classic stone to concrete. It also includes exciting patterns. The Dry Back floors, with a 0.55 mm wear layer, are based on virgin vinyl and constructed in five different layers, topped by a ceramic coating. The result is extremely resilient and strong floors resistant to both scratching and water, which means that these floors are suitable even for spaces exposed to heavy traffic. Just like all our other Luxury Tiles floors, they are phthalate-free.

PRODUCT DETAILS			TECHNICAL PROPERTIES	5
Product type / Construction	Luxury Vinyl Tiles and Planks / Dry Back LVT		Statical electrical	
Article Number / EAN Code	LTDBS3015-457-5 / 7393969113434		propensity	
Design	Tile Design		Chemical resistance	
Width x Length x Thickness	457 x 457 x 2.5 mm		Effect of castor chair	
Weight per package / per	21 kg / 4.2 kg		Resistance to bacteria and	
m2			fungi	
Area per package / per	5.01 m ² / 240.5 m ²		- duresion code floor	
pallet			floor score	
Installation method	Glue-down		O SCO GONDON SERVICES	
Floor heating	Yes			
Wear leayer thickness	0.55 mm			
TECHNICAL PROPERTIES				
Reaction To Fire	EN13501-1	Bfl-s1		
Thermal Resistance R-Value		0.011 (m2K/W)		
Dimensional stability	EN ISO 23999	< 0.1 %		
Colour fastness	EN ISO 105-B02	≥ 6	<u></u>	
Slip resistance	EN 13893	DS (>0.3)		

DIN 51130

Statical electrical EN 1815 < 2 kV (antistatic) propensity Chemical resistance EN ISO 26987 Pass with good results Effect of castor chair EN 425 Suitable Resistance to bacteria and Good fungi





Descriptions & Imagery

Slip resistance

R10

Other products in this collection

