



Pass with good results

Suitable Good

MAKALU DBS 305-030

Our Luxury Tiles Dry Back collection is available in a wide selection of wood and stone designs. The wood designs range from traditional to rustic, while the stone designs span from classic stone to concrete. It also includes exciting patterns. The Dry Back floors, with a 0.55 mm wear layer, are based on virgin vinyl and constructed in five different layers, topped by a ceramic coating. The result is extremely resilient and strong floors resistant to both scratching and water, which means that these floors are suitable even for spaces exposed to heavy traffic. Just like all our other Luxury Tiles floors, they are phthalate-free.

| PRODUCT DETAILS | | | TECHNICAL PROPERTIES | |
|--------------------------------|---------------------------------|---------------------|----------------------------------|--------------|
| Construction | Dry back | | Chemical resistance | EN ISO 26987 |
| Article Number / EAN Code | LTDBS3007-305-3 / 7393969113861 | | Effect of castor chair | EN 425 |
| Design | Stone design | | Resistance to bacteria and fungi | |
| Width x Length x Thickness | 24 x 12 x 1/8" | | | |
| Weight per package / per | 24.3 lbs / 9.3 lbs | | <u> </u> | |
| m2 | | | | |
| Installation method | Glue-Down | | | |
| Floor heating | Yes | | | |
| Wear leayer thickness | 0" | | | |
| TECHNICAL PROPERTIES | | | | |
| Reaction To Fire | EN13501-1 | Bfl-s1 | <u> </u> | |
| Thermal Resistance R-Value | | 0.011 (m2K/W) | | |
| Dimensional stability | EN ISO 23999 | < 0.1 % | | |
| Colour fastness | EN ISO 105-B02 | ≥ 6 | | |
| Slip resistance | EN 13893 | DS (>0.3) | | |
| Slip resistance | DIN 51130 | R10 | | |
| Statical electrical propensity | EN 1815 | < 2 kV (antistatic) | | |

Other products in this collection

