



## SCHWARZHORN DBS 305-030 - 0.3 MM

Our Luxury Tiles Dry Back collection is available in a wide selection of wood and stone designs. The wood designs range from traditional to rustic, while the stone designs span from classic stone to concrete. It also includes exciting patterns. The Dry Back floors, with a 0.55 mm wear layer, are based on virgin vinyl and constructed in five different layers, topped by a ceramic coating. The result is extremely resilient and strong floors resistant to both scratching and water, which means that these floors are suitable even for spaces exposed to heavy traffic. Just like all our other Luxury Tiles floors, they are phthalate-free.

| PRODUCT DETAILS             |  |               |
|-----------------------------|--|---------------|
| Product type / Construction | Luxury Vinyl Tiles and Planks / Dry Back LVT |               |
| Article Number / EAN Code   | LTDBS3008-305-3 / 7393969113878              |               |
| Design                      | Tile Design                                  |               |
| Width x Length x Thickness  | 609 x 305 x 2.5 mm                           |               |
| Weight per package / per    | 11 kg / 4.23 kg                              |               |
| m2                          |  |               |
| Area per package / per      | 2.6 m <sup>2</sup> / 278.6 m <sup>2</sup>    |               |
| pallet                      |  |               |
| Installation method         | Glue-down                                    |               |
| Floor heating               | Yes  |               |
| Wear leayer thickness       | 0.3 mm                                       |               |
| TECHNICAL PROPERTIES        |  |               |
| Reaction To Fire            | EN13501-1                                    | Bfl-s1        |
| Thermal Resistance R-Value  |  | 0.011 (m2K/W) |
| Dimensional stability       | EN ISO 23999                                 | < 0.1 %       |
| Colour fastness             | EN ISO 105-B02                               | ≥ 6           |

EN 13893

DIN 51130

| TECHNICAL PROPERTIES |         |                     |  |
|----------------------|---------|---------------------|--|
| Statical electrical  | EN 1815 | < 2 kV (antistatic) |  |
| propensity           |         |                     |  |

Propensity

Chemical resistance EN ISO 26987 Pass with good results

Resistance to bacteria and Good



fungi



Slip resistance

Slip resistance

DS (>0.3)

R10

## Other products in this collection

