




DOM DBS 457-030 - 0.3 MM

Our Luxury Tiles Dry Back collection is available in a wide selection of wood and stone designs. The wood designs range from traditional to rustic, while the stone designs span from classic stone to concrete. It also includes exciting patterns. The Dry Back floors, with a 0.3 mm wear layer, are based on virgin vinyl and constructed in five different layers, topped by a ceramic coating. The result is extremely resilient and strong floors resistant to both scratching and water, which means that these floors are suitable even for spaces exposed to heavy traffic. Just like all our other Luxury Tiles floors, they are phthalate-free.

PRODUCT DETAILS			TECHNICAL PROPERTIES	
Product type / Construction	Luxury Vinyl Tiles and Planks / Dry Back LVT		Statical electrical	
Article Number / EAN Code	LTDBS3014-457-3 / 7393969113908		propensity	
Design	Tile Design		Chemical resistance	
Width x Length x Thickness	457 x 457 x 2.5 mm		Effect of castor chair	
Weight per package / per	21 kg / 4.2 kg		Resistance to bacteria and	
m2			fungi	
Area per package / per	5 m ² / 240.5 m ²		WHEELON CYAR	and the same of th
pallet			_ :M1>:	floor score
Installation method	Glue-down		A STAM OHIGH	O SCS Gishal Services
Floor heating	Yes		_	
Wear leayer thickness	0.3 mm		<u> </u>	
TECHNICAL PROPERTIES				
Reaction To Fire	EN13501-1	Bfl-s1		
Thermal Resistance R-Value		0.011 (m2K/W)	_	
Dimensional stability	EN ISO 23999	< 0.1 %		
Colour fastness	EN ISO 105-B02	≥ 6	<u> </u>	
Slip resistance	EN 13893	DS (>0.3)	_	

DIN 51130







Descriptions & Imagery

Slip resistance

R10

Other products in this collection

