



DAINTREE DBW 229-030 - 0.3 MM

Our Luxury Tiles Dry Back collection is available in a wide selection of wood and stone designs. The wood designs range from traditional to rustic, while the stone designs span from classic stone to concrete. It also includes exciting patterns. The Dry Back floors, with a 0.55 mm wear layer, are based on virgin vinyl and constructed in five different layers, topped by a ceramic coating. The result is extremely resilient and strong floors resistant to both scratching and water, which means that these floors are suitable even for spaces exposed to heavy traffic. Just like all our other Luxury Tiles floors, they are phthalate-free.

PRODUCT DETAILS			TECHNICAL PROPERTIES
Product type / Construction	Luxury Vinyl Tiles and Planks / Dry Back LVT		Statical electrical
Article Number / EAN Code	LTDBW2106-229-3 / 7393969114035		propensity
Design	Tile Design		Chemical resistance
Width x Length x Thickness	229 x 1219 x 2.5 mm		Resistance to bacteria and
Weight per package / per	16 kg / 4 kg		fungi
m2			SON C/.
Area per package / per	4 m ² / 265.6 m ²		floor M1) score
pallet			G STAM OMOLE
Installation method	Glue-down		_
Floor heating	Yes		_
Wear leayer thickness	0.3 mm		_
TECHNICAL PROPERTIES			_
Reaction To Fire	EN13501-1	Bfl-s1	_
Thermal Resistance R-Value		0.011 (m2K/W)	_
Dimensional stability	EN ISO 23999	< 0.1 %	_
Colour fastness	EN ISO 105-B02	≥ 6	_
Slip resistance	EN 13893	DS (>0.3)	_

DIN 51130

Statical electrical	EN 1815	< 2 kV (antistatic)
propensity		
Chemical resistance	EN ISO 26987	Pass with good results







Slip resistance

R10

Other products in this collection

