



< 2 kV (antistatic)

Suitable

Good

Pass with good results

SAREK DBW 229-030 - 0.3 MM

Our Luxury Tiles Dry Back collection is available in a wide selection of wood and stone designs. The wood designs range from traditional to rustic, while the stone designs span from classic stone to concrete. It also includes exciting patterns. The Dry Back floors, with a 0.55 mm wear layer, are based on virgin vinyl and constructed in five different layers, topped by a ceramic coating. The result is extremely resilient and strong floors resistant to both scratching and water, which means that these floors are suitable even for spaces exposed to heavy traffic. Just like all our other Luxury Tiles floors, they are phthalate-free.

PRODUCT DETAILS			TECHNICAL PROPERTIES
Product type / Construction	Vinyl Flooring / Dry Back	LVT	Statical electrical
Article Number / EAN Code	LTDBW2116-229-3 / 739	93969114141	propensity
Design	Tile Design		Chemical resistance
Width x Length x Thickness	9 x 48 x 1/8"		Effect of castor chair
Weight per package / per	35.3 lbs / 8.8 lbs		Resistance to bacteria and
m2			fungi
Area per package / per	43.1 sqft / 2858.9 sqft		Selon Cope
pallet			floor M1) score
Installation method	Glue-Down		Get appropriate
Floor heating	Yes		_
Wear leayer thickness	0"		_
TECHNICAL PROPERTIES			_
Reaction To Fire	EN13501-1	Bfl-s1	_
Thermal Resistance R-Value		0.011 (m2K/W)	_
Dimensional stability	EN ISO 23999	< 0.1 %	_
Colour fastness	EN ISO 105-B02	≥ 6	_
Slip resistance	EN 13893	DS (>0.3)	_
Slip resistance	DIN 51130	R10	_





EN 1815

EN 425

EN ISO 26987

Other products in this collection





Triglav - Dry back