



# HUMBOLDT DBW 229-030 - 0.3 MM

Our Luxury Tiles Dry Back collection is available in a wide selection of wood and stone designs. The wood designs range from traditional to rustic, while the stone designs span from classic stone to concrete. It also includes exciting patterns. The Dry Back floors, with a 0.55 mm wear layer, are based on virgin vinyl and constructed in five different layers, topped by a ceramic coating. The result is extremely resilient and strong floors resistant to both scratching and water, which means that these floors are suitable even for spaces exposed to heavy traffic. Just like all our other Luxury Tiles floors, they are phthalate-free.

## PRODUCT DETAILS

|                               |  |
|-------------------------------|--|
| Product type / Construction   | Luxury Vinyl Tiles and Planks / Dry Back LVT |
| Article Number / EAN Code     | LTDBW2125-229-3 / 7393969114226              |
| Design                        | Tile Design                                  |
| Width x Length x Thickness    | 229 x 1219 x 2.5 mm                          |
| Weight per package / per m2   | 16 kg / 4 kg                                 |
| Area per package / per pallet | 4 m² / 265.6 m²                              |
| Installation method           | Glue-down                                    |
| Floor heating                 | Yes  |
| Wear leayer thickness         | 0.3 mm                                       |

## TECHNICAL PROPERTIES

|                            |                |               |
|----------------------------|----------------|---------------|
| Reaction To Fire           | EN13501-1      | Bfl-s1        |
| Thermal Resistance R-Value |                | 0.011 (m2K/W) |
| Dimensional stability      | EN ISO 23999   | < 0.1 %       |
| Colour fastness            | EN ISO 105-B02 | ≥ 6           |
| Slip resistance            | EN 13893       | DS (>0.3)     |
| Slip resistance            | DIN 51130      | R10           |

## TECHNICAL PROPERTIES

|                                  |              |                        |
|----------------------------------|--------------|------------------------|
| Statical electrical propensity   | EN 1815      | < 2 kV (antistatic)    |
| Chemical resistance              | EN ISO 26987 | Pass with good results |
| Resistance to bacteria and fungi |              | Good                   |



### Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.

Other products in this collection



SAPO - DRY BACK



HANMER - DRY BACK



MOESGAARD - DRY BACK



FONTIN - DRY BACK



THURINGIAN - DRY BACK



COCONINO - DRY BACK



FOLOI - DRY BACK



BLAIKEN - DRY BACK



KILSBERGEN - DRY BACK



AKKELIS - DRY BACK



STANTON - DRY BACK



DURMITOR - DRY BACK



CALDER - DRY BACK



TIVEDEN - DRY BACK



CORMORANT - DRY BACK



YUKON - DRY BACK



TAIGA - DRY BACK



BELLUNO - DRY BACK



WENTWOOD - DRY BACK



SCHWARZWALD - DRY BACK



SAXON - DRY BACK



SAREK - DRY BACK



REDWOOD - DRY BACK



OULANKA - DRY BACK



WHINFELL - DRY BACK



HUMBOLDT - DRY BACK



PLITVICE - DRY BACK



TRIGLAV - DRY BACK