



CORMORANT DBW 229-030 - 0.3 MM

Our Luxury Tiles Dry Back collection is available in a wide selection of wood and stone designs. The wood designs range from traditional to rustic, while the stone designs span from classic stone to concrete. It also includes exciting patterns. The Dry Back floors, with a 0.3 mm wear layer, are based on virgin vinyl and constructed in five different layers, topped by a ceramic coating. The result is extremely resilient and strong floors resistant to both scratching and water, which means that these floors are suitable even for spaces exposed to heavy traffic. Just like all our other Luxury Tiles floors, they are phthalate-free.

PRODUCT DETAILS			TECHNIC	CAL PROPERTIES
Product type / Construction	Luxury Vinyl Tiles and Planks / Dry Back LVT		Statical electrical	
Article Number / EAN Code	LTDBW2128-229-3 / 7393969114240		propensity	
Design	Plank		Chemical resistance	
Width x Length x Thickness	229 x 1219 x 2.5 mm		Effect of castor chair	
Weight per package / per	16 kg / 4 kg		Resistance to bacteria and	
m2			fungi	
Area per package / per	3.9 m ² / 265.6 m ²		- 610N C/	
pallet			; M1> 2	floor score
Installation method	Glue-down		WASTAM OMICIE	O CONTROL OF Services
Floor heating	Yes		_	
Wear leayer thickness	0.3 mm		_	
TECHNICAL PROPERTIES			_	
Reaction To Fire	EN13501-1	Bfl-s1	_	
Thermal Resistance R-Value		0.011 (m2K/W)	_	
Dimensional stability	EN ISO 23999	< 0.1 %	_	
Colour fastness	EN ISO 105-B02	≥ 6	_	

EN 13893

DIN 51130

Statical electrical	EN 1815	< 2 kV (antistatic)
propensity		
Chemical resistance	EN ISO 26987	Pass with good results
Effect of castor chair	EN 425	Suitable
Resistance to bacteria and		Good
fungi		





Descriptions & Imagery

Slip resistance

Slip resistance

DS (>0.3)

R10

Other products in this collection





HUMBOLDT - DRY BACK

PLITVICE - DRY BACK

TRIGLAV - DRY BACK