



## CORMORANT DBW 229-030 - 0.3 MM

Our Luxury Tiles Dry Back collection is available in a wide selection of wood and stone designs. The wood designs range from traditional to rustic, while the stone designs span from classic stone to concrete. It also includes exciting patterns. The Dry Back floors, with a 0.55 mm wear layer, are based on virgin vinyl and constructed in five different layers, topped by a ceramic coating. The result is extremely resilient and strong floors resistant to both scratching and water, which means that these floors are suitable even for spaces exposed to heavy traffic. Just like all our other Luxury Tiles floors, they are phthalate-free.

| PRODUCT DETAILS    |   | TECHNICAL PROPERTIES       |                                  |                        |  |
|--------------------|---|----------------------------|----------------------------------|------------------------|--|
| Article Number     | LTDBW2128-229-3                             | Reaction To Fire           | EN13501-1                        | Bfl-s1                 | B <sub>II</sub> -s1  |
| Dimensions         | 9 x 48 "                                    | Thermal Resistance R-Value |                                  | 0.011 (m2K/W)          |  |
| Weight per Package | 35.3 lbs                                    | Dimensional stability      | EN ISO                           | < 0.1 %                | K N  |
| Area per Package   | 43.1 sqft                                   |                            | 23999                            |                        |  |
| Area per pallet    | 2858.9 sqft                                 | Colour fastness            | EN ISO 105-<br>B02               | ≥ 6                    | <b>\$</b>  |
| Construction       | Dry back                                    | Slip resistance            | EN 13893                         | DS (>0.3)              | The state of the s |
| FACTS              |   | Slip resistance            | DIN 51130                        | R10                    | 12 m   |
| Design             | Wood design                                 | Statical electrical        | EN 1815                          | < 2 kV (antistatic)    | <b>F</b>   |
| Range              | Luxury Tiles                                | propensity                 | LIVIOIS                          | 12 KV (diffusioner)    |  |
| Collection         | Dry Back Wood Collection -<br>Special Order | Chemical resistance        | EN ISO<br>26987                  | Pass with good results | Ð  |
| Floor heating      | Yes   | Resistance to bacteria     | Resistance to bacteria and fungi |                        |  |
| Thickness          | 1/8"  |                            |                                  |                        |  |

## **Descriptions & Imagery**

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.





FACTS TECHNICAL PROPERTIES

Installation method

Glue-Down

## **Descriptions & Imagery**

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.



