



Pass with good results

Suitable

Good

EN ISO 26987

EN 425

SHERWOOD DBW 229-030 - 0.3 MM

Our Luxury Tiles Dry Back collection is available in a wide selection of wood and stone designs. The wood designs range from traditional to rustic, while the stone designs span from classic stone to concrete. It also includes exciting patterns. The Dry Back floors, with a 0.55 mm wear layer, are based on virgin vinyl and constructed in five different layers, topped by a ceramic coating. The result is extremely resilient and strong floors resistant to both scratching and water, which means that these floors are suitable even for spaces exposed to heavy traffic. Just like all our other Luxury Tiles floors, they are phthalate-free.

PRODUCT DETAILS			TECHNICAL PROPERTIES
Product type / Construction	Vinyl Flooring / Dry Back LVT		Chemical resistance
Article Number / EAN Code	LTDBW2003-229-3 / 7393969114394		Effect of castor chair
Design	Tile Design		Resistance to bacteria and
Width x Length x Thickness	9 x 48 x 1/8"		fungi
Weight per package / per	35.3 lbs / 8.8 lbs		
m2			
Installation method	Glue-Down		
Floor heating	Yes		
Wear leayer thickness	0"		<u></u>
TECHNICAL PROPERTIES			
Reaction To Fire	EN13501-1	Bfl-s1	
Thermal Resistance R-Value		0.011 (m2K/W)	
Dimensional stability	EN ISO 23999	< 0.1 %	
Colour fastness	EN ISO 105-B02	≥ 6	
Slip resistance	EN 13893	DS (>0.3)	
Slip resistance	DIN 51130	R10	
Statical electrical propensity	EN 1815	< 2 kV (antistatic)	

Other products in this collection





Triglav - Dry back