



QUARTZ MOSAIC 8319 SPINEL BLACK 12 X 12

PRODUCT DETAILS

The versatile Mosaic range includes a wide variety of non-dimensional and colorful designs. While the striped, tone-on-tone tinted granulates soften the visual appearance they also hide dirt efficiently, making Mosaic suitable even for the most demanding areas and situations.

TECHNICAL PROPERTIES

Article Number108319Reaction To FireEN13501-1Bfl-s1EAN Code6418660251795Residual indentationEN ISO 24343-1< 0.05 mm	PRODUCT DETAILS		TECHNICAL PROPERTIES		
Dimensions24343-1Weight per Package47.4 lbsDimensional stabilityEN ISO 23999<0.2%	Article Number	108319	Reaction To Fire	EN13501-1	Bfl-s1
Dimensions12 x 12 "Weight per Package47.4 lbsDimensional stabilityEN ISO 23999<0.2%	EAN Code	6418660251795	Residual indentation		< 0.05 mm
Weight per Package 47.4 lbs 23999 Area per Package 58 sqft Colour fastness EN ISO 105- ≥ 6 B02 Area per pallet 2609.9 sqft Slip resistance EN 13893 DS (>0.3) Package info Statical electrical propensity EN 1815 < 2 kV (antistatic)	Dimensions	12 x 12 "		24343-1	
Area per pallet Package info Packages may contain start and stop boards. FACTS Collection Quartz Mosaic Collection Thickness 1/8" Collection Collection	Weight per Package	47.4 lbs	Dimensional stability		<0.2%
Package info Packages may contain start and stop boards. Slip resistance Statical electrical propensity FACTS Collection Quartz Mosaic Collection Thickness 1/8" Slip resistance EN 13893 DS (>0.3) EN 1815 < 2 kV (antistatic) Excellent 26987 Effect of castor chair EN 425 Suitable (25.000 cycles)	Area per Package	58 sqft	Colour fastness	EN ISO 105-	≥ 6
FACTS Collection Quartz Mosaic Collection Thickness 1/8" Statical electrical propensity Chemical resistance EN 1815 C kV (antistatic) Excellent 26987 Excellent Suitable (25.000 cycles)	Area per pallet	2609.9 sqft		B02	
FACTS Collection Quartz Mosaic Collection Thickness 1/8" Chemical resistance EN ISO 26987 Excellent 26987 Excellent EN 425 Suitable (25.000 cycles)	Package info		Slip resistance	EN 13893	DS (>0.3)
Collection Quartz Mosaic Collection Chemical resistance EN ISO 26987 Excellent Thickness 1/8" Effect of castor chair EN 425 Suitable (25.000 cycles)	FACTS			EN 1815	< 2 kV (antistatic)
Thickness 1/8" Effect of castor chair EN 425 Suitable (25.000 cycles)	FAC15		Chemical resistance	EN ISO	Excellent
Liter of Castor Chair En 425 Suitable (25.000 Cycles)	Collection	Quartz Mosaic Collection		26987	
LRV 6.4 Resistance to bacteria and fungi Good	Thickness	1/8"	Effect of castor chair	EN 425	Suitable (25.000 cycles)
	LRV	6.4	Resistance to bacteria and fungi		Good

Other products in this collection



AB GUSTAF KÄHR | www.kahrs.com | © Kährs 2023



Quartz Mosaic 8314 Thunder



Quartz Mosaic 8315 Lava Grey



Quartz Mosaic 8317 Zebra Jasper



Quartz Mosaic 8319 Spinel Black



Quartz Mosaic 8353 Blue Chalcedony



Quartz Mosaic 8357 Blue

CERTIFICATES











Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.